

### Lake Hancock Road Phosphorus Loading Calculations

Existing Condition	Land Use	Soil Type	Total P Loading (kg/ac-yr)		Basin Acreage (acres)		Inflow Mass Loading (kg/yr)		Treatment System	Inches of Retention Over Basin Area (inches)	Pollutant Removal Efficiency (%)	Outflow Mass Loading (kg/yr)
SkyRidge	HWY 75%	HSG A	1.053	X	3.35	=	3.53		Dry Retention	1.00	83	0.60
SkyRidge	OPEN	HSG A	0.004	X	3.56	=	0.01		Dry Retention	1.00	96	0.00
Basin 1	OPEN	HSG A	0.004	X	14.28	=	0.06					0.06
Basin 2	OPEN	HSG A	0.004	X	13.48	=	0.05					0.05
Big Sky	SFR 40%	HSG A	0.25	X	1.88	=	0.47		Dry Retention	2.57	97	0.01
Basin 4A (The Reserve)	HWY 75%	HSG A	1.053	X	1.29	=	1.36		Dry Retention	11.00**	100	0.00
Basin 4B (The Reserve)	OPEN	HSG A	0.004	X	1.05	=	0.00		Dry Retention	11.00**	100	0.00
					<b>38.89</b>		<b>5.48</b>					<b>0.73</b>
Proposed Condition	Land Use	Soil Type	Total P Loading (kg/ac-yr)		Basin Acreage (acres)		Inflow Mass Loading (kg/yr)		Treatment System	Inches of Retention Over Basin Area (inches)	Pollutant Removal Efficiency (%)	Outflow Mass Loading (kg/yr)
SkyRidge	HWY 75%	HSG A	1.053	X	3.26	=	3.43		Dry Retention	1.00	83	0.58
SkyRidge	OPEN	HSG A	0.004	X	3.65	=	0.01		Dry Retention	1.00	96	0.00
Basin 1A	HWY 75%	HSG A	1.053	X	3.36	=	3.54		Dry Retention	4.69**	100	0.00
Basin 1B	OPEN	HSG A	0.004	X	10.92	=	0.04		Dry Retention	4.69**	100	0.00
Basin 2A	HWY 75%	HSG A	1.053	X	10.43	=	10.98		Dry Retention	7.41**	100	0.00
Basin 2B	OPEN	HSG A	0.004	X	5.42	=	0.02		Dry Retention	7.41**	100	0.00
Basin 4A (The Reserve)	HWY 75%	HSG A	1.053	X	1.26	=	1.33		Dry Retention	11.00**	100	0.00
Basin 4B (The Reserve)	OPEN	HSG A	0.004	X	0.59	=	0.00		Dry Retention	11.00**	100	0.00
					<b>38.89</b>		<b>19.36</b>					<b>0.58</b>

\*\* = Since inches treated is >4.0", assume 100% removal per Table 11.7-1, Page 11-30 of MSSW Handbook.

James E. Myers, P.E. (PE#44751)  
 TLP Engineering Consultants, Inc.  
 3208 W. SR426, Suite 1020  
 Oviedo, FL 32765  
 407-951-8811

50126-4  
 RECEIVED  
 JUN 15 2011  
 ALTAMONTE