

Residential Driveway Apron Permit Application (Please Print or Type)

SEP	1-8 2017
	JIN 28 233
PUB	AKE COUNTY LIC WORKS DEPARTMENT

Date: Bldg Permit 200 1 7 0	9 0 3 7 0	PUBLIC V	VORKS DEPARTMENT						
LINDA CAMPBELL	2695790 ,04	4 ,24	,25						
Applicant/ Name Permit Will Be Returned To:		ction Township	Range						
P.O. BOX 1074	5235 C	COUNTY RD 561							
Applicant's Street Address	House Number / Road Name								
KATHLEEN, FL 33849	Trustees								
Applicant's City, State, Zip	Subdivision Name								
863-581-75444	LINDA CAMPBELL								
Signature of Applicant Phone Number	Applicant, Please Print Name								
EARNITALL23@AOL.COM	IH-1025311								
Applicant's e-mail address	Contractor License	# (Required unles	s built by owner)						
A driveway permit is required to construct a new driveway, modify an existing driveway to meet county requirements, or install a temporary construction entrance within the public rights-of-way of County maintained roads. Issuance of a driveway permit does not vest any rights to the property owner for zoning, land use changes, or site improvements. The owner must follow all County procedures for permitting.									
Driveway must be constructed in accordance with the Lake County Land Development Regulations and as shown on the attached sketch. Applicant holds Lake County harmless from all damages, claims, or injuries which may result from such work. Any deviation from the attached sketch must first be approved in writing by Lake County Public Works Department. Please see attached minimum requirement details for specifications. Check one: Clay Road — No apron required — culvert pipe may be required — sod all disturbed areas. Paved Road — Option 1: 6" limerock base and minimum 1" Type S-III Asphalt. Option 2: 6"reinforced concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of existing pavement. Culvert pipe may be required — Sod all disturbed areas.									
In areas where sidewalks are present or planned, the drived driveway apron (at a maximum 1.5% cross slope) in compliant	veway must include a mir ance with ADA requirement	imum 4 foot wide p s.	path traversing the						
County Road # 0634 To be compl	leted by County Staff								
Driveway Permit Fee: \$50.00 Check/Transaction #:	5/8 407 Date: 1	1/2/17 Fee	e Code: PUBSV1						
	ned:	Date App	roved:						
Permit Shall Expire One (1) Year From Date Approved	Date Expired:								
Date of Final Inspection: Inspector:									
Comments or special conditions:									
The design has been reviewed and upon completion shapplication. The driveway shall be constructed per app County Building Services Division at 352-343-9634. For Public Works Department at 352-253-6019. Submit permit to: Lake County Public Works, Post O.	proved subdivision plans or joint (Common Split)	if applicable. For i driveway inspectio	nspection, call Lake						

near Client

Public Works Department Road Operations Division Residential Driveway Apron Permit Effective June 2015



Residential Driveway Apron Permit Application Requirements

To be completed by County Staff								
☐ Single Family Driveway (standard A) ☐ Joint Driveway (Common/Split) (standard B)	20	_		0 ! nit l				0
 □ Driveway apron as Swale Check (standard C) □ Piped Driveway apron (standard D) □ Driveway apron conforming to Grade or Swale (standard 	E)							
☐ Driveway apron with Miami Curb & Gutter (standard M) ☐ Driveway apron with Standard Curb & Gutter (standard s	S)							
*The applicable driveway apron standard will be included with approv	<u>ed per</u>	mit	tha	at is	ser	nt to	арр	licant. *

- 1. Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment).
- 2. To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
- 3. Driveways are not permitted in the radius return of an intersection. Driveway aprons must be 100 feet from the nearest intersecting road and may not exceed 24 feet in width at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
- 4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
- 5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
- 6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
- 7. Driveway permit shall expire one (1) year from date approved.
- 8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements of

9-15-17

Applicant's Signature/Date