

## **Residential Driveway Apron** Permit Application (Please Print or Type)

LAKE COUNTY

Date: $11/9/17$ Bldg Permit No. $20170$	80912 PUBLIC WORKS DEPARTMENT			
Adams Homes of Northwest Florida Applicant/ Name Permit Will Be Returned To:	Alt. Key# Section Township Range			
4401 Vine and Rd Suite A-11 Applicant's Street Address	Alt. Key# Section Township Range  7709 5 loewood Drive.  House Number / Road Name			
Orlando, FL 32811 Applicant's City, State, Zip	Pork Hill Phase 2 Subdivision Name			
Signature of Applicant Phone Number	Teffrey Nedges Applicant, Please Print Name			
Orlandowarranty a adamshones. com Applicant's e-mail address	CRC 1330146  Contractor License # (Required unless built by owner)			
A driveway permit is required to construct a new driveway, modify an existing driveway to meet county requirements, or install a temporary construction entrance within the public rights-of-way of County maintained roads. Issuance of a driveway permit does not vest any rights to the property owner for zoning, land use changes, or site improvements. The owner must follow all County procedures for permitting.				
work. Any deviation from the attached sketch must first be Please see attached minimum requirement details for specific Check one:  Clay Road — No apron required — culvert pipe may Payed Road — Option 1: 6" limerock base and a	be required – sod all disturbed areas.  minimum 1" Type S-III Asphalt. Option 2: 6"reinforced			
In areas where sidewalks are present or planned, the drive driveway apron (at a maximum 1.5% cross slope) in complian	eway must include a minimum 4 foot wide path traversing the nce with ADA requirements.			
County Road # 49244 To be complete	ted by County Staff			
Driveway Permit Fee: \$50.00 Check/Transaction#:	19129 Date: 11/9/17 Fee Code: PUBSV1			
Permit # 15766 Maint Area: Signed				
Permit Shall Expire One (1) Year From Date Approved	Date Expired:			
Date of Final Inspection: Inspector				
Comments or special conditions:				
The design has been reviewed and upon completion show application. The driveway shall be constructed per approx County Building Services Division at 352-343-9634. For j. Public Works Department at 352-253-6010.	ald meet the regulations, and requirements as noted on this			

Public Works Department Road Operations Division

Entered Data One irst Scan	6/28/18 U18/18
edated Data One	
cond Scan	
tuned to Client	

Submit permit to: Lake County Public Works, Post Office Box 7800, Tavares, FL 32778

Residential Driveway Apron Permit Effective June 2015



## **Residential Driveway Apron Permit Application Requirements**

To be completed by County Staff			
☐ Single Family Driveway (standard A)☐ Joint Driveway (Common/Split) (standard B)	Permit Number		
<ul> <li>Driveway apron as Swale Check (standard C)</li> <li>Piped Driveway apron (standard D)</li> <li>Driveway apron conforming to Grade or Swale (standard E)</li> </ul>			
☐ Driveway apron with Miami Curb & Gutter (standard M) ☐ Driveway apron with Standard Curb & Gutter (standard S)			
*The applicable driveway apron standard will be included with approved per	rmit that is sent to applicant. *		

- 1. Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment).
- 2. To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
- 3. Driveways are not permitted in the radius return of an intersection. With the exception of joint driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10 feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4 foot wide flares on either side of the driveway, for a maximum width of 32' at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
- 4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
- 5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
- 6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
- 7. Driveway permit shall expire one (1) year from date approved.
- 8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements		
	Applicant's Signature/Date	