

Residential Driveway Apron Permit Application

SEF 1 8 20

(Please Print or Type) 2017090336

Date: Bldg Permit No. 2017080	9913 PUBLIC VOS LO DEPARTA
Jeffrey Hedges Name Permit Will Be Returned To:	/29 /19 /25 County Road # Section Township Range
4401 Vineland Rd Suite A-11	31704 Parkdale Drive
Street Address	House Number / Road Name
Orlando FL 32811	Park Hill Phase I , Lot 35
City, State, Zip	Subdivision Name
	Jeffrey Hedges
Signature Of Applicant Phone Number	Applicant, Please Print Name
orlandowarranty@adamshomes.com	

A driveway permit is required to construct a new driveway, modify an existing driveway to meet county requirements, or install a temporary construction entrance within the public rights-of-way of County maintained roads. Issuance of a driveway permit does not vest any rights to the property owner for zoning, land use changes, or site improvements. The owner must follow all County procedures for permitting.

Driveway must be constructed in accordance with the Lake County Land Development Regulations and as shown on the attached sketch. Applicant holds Lake County harmless from all damages, claims, or injuries which may result from such work. Any deviation from the attached sketch must first be approved in writing by Lake County Public Works Department. Please see attached minimum requirement details for specifications.

Check one:

Applicant's e-mail address

Clay Road – No apron required – culvert pipe may be required – sod all disturbed areas.

☑ Paved Road — Option 1: 6" limerock base and minimum 1" Type S-III Asphalt. Option 2: 6"reinforced concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of existing pavement. Culvert pipe may be required — Sod all disturbed areas.

In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 2% cross slope) in compliance with ADA requirements.

4523B To be completed by County Staff			
Driveway Permit Fee: \$50.00 Check Number: 519125 Date: 11/9/17 Fee Code: PUBSV1			
Permit # 15767 Maint Area: Signed: Date Approved:			
Permit Shall Expire One (1) Year From Date Approved Date Expired:			
Date of Final Inspection: Inspector:			
Comments or special conditions:			
The design has been reviewed and upon completion should meet the regulations and requirements as noted on this application. The driveway shall be constructed per approved subdivision plans if applicable. For inspection, call Lake County Building Services Division at 352-343-9634. For joint (Common Split) driveway inspection, call Lake County Public Works Department at 352-483-9000. Submit permit to Lake County Public Works, 437 Ardice Avenue, Eustis, FL 32726			

Public Works Department Funding & Production Division

ntorad Data One	6/28/18
si 51. 11	6/28/18
valor date One	
and Scan	Management of the second strategy and the second strategy are second strategy and the second strategy are second strategy and the second strategy and
and a Clions	

Residential Driveway Apron Permit Effective July 2012



Residential Driveway Apron Permit Application Requirements

☐ Single Family Driveway (standard A)☐ Joint Driveway (Common/Split) (standard B)	2017090336
 ☑ Driveway apron as Swale Check (standard C) ☑ Piped Driveway apron (standard D) ☑ Driveway apron conforming to Grade or Swale (standard 	SEP 1 8 2017
 Driveway apron with Miami Curb & Gutter (standard M) Driveway apron with Standard Curb & Gutter (standard 	••
The applicable driveway apron standard will be included with approv	ved permit that is sent to applicant. *

- Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 2%, 6 inches 1. minimum thickness. (See detail on attachment).
- 2. To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 437 Ardice Avenue in Eustis.
- Driveways are not permitted in the radius return of an intersection. Driveway aprons must be 100 3. feet from the nearest intersecting road and may not exceed 24 feet in width at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
- Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or 4. repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
- 5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
- 6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 2% cross slope) in compliance with ADA requirements.
- 7. Driveway permit shall expire one (1) year from date approved.
- 8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements