



Residential Driveway Apron Permit Application (Please Print or Type)



Date: _____

Bldg Permit No. 2017101364

HOME DYNAMICS

Name Permit Will Be Returned To:

4755 TECHNOLOGY WAY #210

Street Address

BOCA RATON, FL 33431

City, State, Zip

(954)

914-0246

Signature Of Applicant

Phone Number

igarcia@homedynamics.com

Applicant's e-mail address

3906052

Alt. Key# Section Township Range

16013 Champlain ST

House Number / Road Name

GREATER LAKES

LOT 267

Subdivision Name

ISMAEL GARCIA

Applicant, Please Print Name

Contractor License # (Required unless built by owner)

A driveway permit is required to construct a new driveway, modify an existing driveway to meet county requirements, or install a temporary construction entrance within the public rights-of-way of County maintained roads.

Driveway must be constructed in accordance with the Lake County Land Development Regulations and as shown on the attached sketch.

Check one:

[X] Clay Road - No apron required - culvert pipe may be required - sod all disturbed areas.

[X] Paved Road - Option 1: 6" limerock base and minimum 1" Type S-III Asphalt. Option 2: 6" reinforced concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of existing pavement.

In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.

County Road # 0357K To be completed by County Staff
Driveway Permit Fee: \$50.00 Check/Transaction #: 519377 Date: 11/16/17 Fcc Code: PUBSV1
Permit # 15772 Maint Area: 2 Signed: Date Approved:
Permit Shall Expire One (1) Year From Date Approved Date Expired:
Date of Final Inspection: Inspector:
Comments or special conditions:
The design has been reviewed and upon completion should meet the regulations and requirements as noted on this application.

Public Works Department Road Operations Division

Entered Data One 6/28/18
Checked 6/28/18

Residential Driveway Apron Permit Effective February 2015

2017/01/30/14



Residential Driveway Apron Permit Application Requirements

To be completed by County Staff

- Single Family Driveway (standard A)
- Joint Driveway (Common/Split) (standard B)
- Driveway apron as Swale Check (standard C)
- Piped Driveway apron (standard D)
- Driveway apron conforming to Grade or Swale (standard E)
- Driveway apron with Miami Curb & Gutter (standard M)
- Driveway apron with Standard Curb & Gutter (standard S)

Permit Number

*The applicable driveway apron standard will be included with approved permit that is sent to applicant. *

1. Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment).
2. To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 437 Ardice Avenue in Eustis.
3. Driveways are not permitted in the radius return of an intersection. Driveway aprons must be 100 feet from the nearest intersecting road and may not exceed 24 feet in width at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
7. Driveway permit shall expire one (1) year from date approved.
8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements

Applicant's Signature/Date

[Handwritten Signature] 10/17/17