




Residential Driveway Apron Permit Application (Please Print or Type)

2017110977



Date: 11/10/17

Bldg Permit No. _____

D.R. Horton, Inc. Agent Carol Marks

Applicant/ Name Permit Will Be Returned To:

6200 Lee Vista Blvd. #400

Applicant's Street Address

Orlando, FL 32822

Applicant's City, State, Zip

Signature of Applicant (407) 850-5238 Phone Number

cdmarks@drhorton.com

Applicant's e-mail address

3905866 / / / Alt. Key# Section Township Range

16140 Yelloweyed Drive House Number / Road Name

Sawgrass Bay / 426 Subdivision Name

Carol Marks Applicant, Please Print Name

CBC1252212 Contractor License # (Required unless built by owner)

A driveway permit is required to construct a new driveway, modify an existing driveway to meet county requirements, or install a temporary construction entrance within the public rights-of-way of County maintained roads.

Driveway must be constructed in accordance with the Lake County Land Development Regulations and as shown on the attached sketch.

Check one:

- Clay Road - No apron required - culvert pipe may be required - sod all disturbed areas.
Paved Road - Option 1: 6" limerock base and minimum 1" Type S-III Asphalt. Option 2: 6" reinforced concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of existing pavement.

In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.

County Road # 0360D To be completed by County Staff
Driveway Permit Fee: \$50.00 Check/Transaction #: 521346 Date: 11/16/17 Fee Code: PUBSV1
Permit # 15801 Maint Area: 2 Signed: Date Approved:
Permit Shall Expire One (1) Year From Date Approved Date Expired:
Date of Final Inspection: Inspector:
Comments or special conditions:
The design has been reviewed and upon completion should meet the regulations and requirements as noted on this application.

Public Works Department Road Operations Division

Residential Driveway Apron Permit Effective February 2017

Entered Data On: 6/28/18
Print Scan: 6/28/18
Printed Data:
Print Scan:

NOV 20 2017



Residential Driveway Apron Permit Application Requirements

To be completed by County Staff **2017110977**

- Single Family Driveway (standard A)**
- Joint Driveway (Common/Split) (standard B)**
- Driveway apron as Swale Check (standard C)**
- Piped Driveway apron (standard D)**
- Driveway apron conforming to Grade or Swale (standard E)**
- Driveway apron with Miami Curb & Gutter (standard M)**
- Driveway apron with Standard Curb & Gutter (standard S)**

Permit Number

*The applicable driveway apron standard will be included with approved permit that is sent to applicant. *

1. Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment).
2. To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
3. Driveways are not permitted in the radius return of an intersection. With the exception of joint driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10 feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4 foot wide flares on either side of the driveway, for a maximum width of 32' at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
7. Driveway permit shall expire one (1) year from date approved.
8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements *[Signature]* **11/10/17**

Applicant's Signature/Date

Public Works Department
Road Operations Division

Residential Driveway Apron Permit
Effective February 2017