

Driveway Apron Application Print or Type)

	Residential Driveway Apron
	Permit Application
AKE COUNTY	(Please Print or Type)
Date: 1-04-18	Bldg Permit No. 201710(385

Anna Caraca	Charles When I have been
	JIN 29 200
PUB	LAKE COUNTY LOWOSIS GES ARTHUS TO

Applicant/ Name Permit Will Be Returned To:	3853519 / 29 / 18 / 26 Alt. Key# Section Township Range			
28 E. Washington St. Applicant's Street Address	37109 Scenic Bluff Dr. House Number / Road Name			
Orlando FL 3280 Applicant's City, Spate, Zip	Windy Ridge / 109 Subdivision Name			
Signature of Applicant Phone Number	Jeffery L. Huebner Applicant, Please Print Name			
Applicant's e-mail address	CBC05789 (Contractor License # (Required unless built by owner)			
A driveway permit is required to construct a new driveway, modify an existing driveway to meet county requirements, or install a temporary construction entrance within the public rights-of-way of County maintained roads. Issuance of a driveway permit does not vest any rights to the property owner for zoning, land use changes, or site improvements. The owner must follow all County procedures for permitting.				
Driveway must be constructed in accordance with the Lake County Land Development Regulations and as shown on the attached sketch. Applicant holds Lake County harmless from all damages, claims, or injuries which may result from such work. Any deviation from the attached sketch must first be approved in writing by Lake County Public Works Department. Please see attached minimum requirement details for specifications.				
Check one: Clay Road — No apron required — culvert pipe may be required — sod all disturbed areas. Paved Road — Option 1: 6" limerock base and minimum 1" Type S-III Asphalt. Option 2: 6"reinforced concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of existing pavement. Culvert pipe may be required — Sod all disturbed areas.				
In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.				
driveway apron (at a maximum 1.5% cross slope) in complia	veway must include a minimum 4 foot wide path traversing the ance with ADA requirements.			
County Road # 6746C To be complete.	eted by County Staff			
County Road # 6746C To be complete.	ance with ADA requirements.			
County Road # 6746 To be completed Driveway Permit Fee: \$50.00 Check/Transaction #:	eted by County Staff			
County Road # 6746 To be completed Driveway Permit Fee: \$50.00 Check/Transaction #:	eted by County Staff Date: 1/8/18 Fee Code: PUBSV1 Date Approved:			
County Road # 5746 To be completed Driveway Permit Fee: \$50.00 Check/Transaction #: Sign	eted by County Staff Date: 1/8/18 Fee Code: PUBSV1 Date Expired:			
County Road # 5746 To be completed To be compl	eted by County Staff Date: 1/8/18 Fee Code: PUBSV1 Date Expired:			
County Road #	eted by County Staff Date: 1/8/18 Fee Code: PUBSV1 Date Expired:			
County Road #	eted by County Staff Society Date 1/8/8			



Residential Driveway Apron Permit Application Requirements

FLORIBA Fermit Application Requirements			
	To be completed by County Staff	2017101288	
	Single Family Driveway (standard A) Joint Driveway (Common/Split) (standard B)	$\frac{201710}{\text{Permit Number}}$	
	Driveway apron as Swale Check (standard C) Piped Driveway apron (standard D) Driveway apron conforming to Grade or Swale (standard E)	-	
	Driveway apron with Miami Curb & Gutter (standard M) Driveway apron with Standard Curb & Gutter (standard S)		
*The applicable driveway apron standard will be included with approved permit that is sent to applicant. *			
1.	Sidewalks must be constructed per FDOT Index 310, with maximum minimum thickness. (See detail on attachment).	cross slope of 1.5%, 6 inches	

- 2. To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
- 3. Driveways are not permitted in the radius return of an intersection. With the exception of joint driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10 feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4 foot wide flares on either side of the driveway, for a maximum width of 32' at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
- 4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
- 5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
- 6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
- 7. Driveway permit shall expire one (1) year from date approved.

8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements

Applicant's Signature/Date

Residential Driveway Apron Permit Effective February 2017

Public Works Department Road Operations Division