

## Residential Driveway Apron Permit Application (Please Print or Type)

j	1 hem had been been been freed
	18 S 20140
	JAN 25 2010 UBLIC WORKS DEPARTMENT

Date: Bldg Permit No. 201	18011248 PUBLIC WORKS DEPARTME									
Carl Ludeote - Charle Township, Applicant/ Name Permit Will Be Returned To:	Wor 367371/3 O2 , 18 , 25 Alt. Key# Section Township Range									
18650 Nury 441 Applicant's Street Address	40710 Thomas Boat Landing Rd House Number / Road Name									
Mt-Dora FL 32757 Applicant's City, State, Zip 352	Subdivision Name									
383-6104 Signature of Applicant Phone Number	Applicant, Please Print Name									
<u>c'ibhowes@aol.co</u> w Applicant's e-mail address	CBC 021054 Contractor License # (Regulred unless built by owner)									
install a temporary construction entrance within the public	ay, modify an existing driveway to meet county requirements, or rights-of-way of County maintained roads. Issuance of a driveway zoning, land use changes, or site improvements. The owner must									
attached sketch. Applicant holds Lake County harmless work. Any deviation from the attached sketch must first Please see attached minimum requirement details for speci Check one:  Clay Road — No apron required — culvert pipe must paved Road — Option 1: 6" Ilmerock base and	ay be required – sod all disturbed ereas, I minimum 1." Type 5-III Asphalt. Option 2: 6"reinforced " wire mesh placed a minimum of 10" from edge of existing									
In areas where sidewalks are present or planned, the driveway apron (at a maximum 1.5% cross slope) in compl	riveway must include a minimum 4 foot wide path traversing the lance with ADA requirements.									
County Road # 7940 To be comp	pleted by County Staff									
Driveway Permit Fee: \$50.00 Check/Transaction#:	52724/ Date 3/15/18 Fee Code: PUBSVI									
Permit # 1553 L Maint Area: 3 Signed: Date Approved: 7/23//8										
Permit Shall Expire One (1) Year From Date Approved Date Expired: 7/23/19										
Date of Final Inspection: Inspector:										
Comments or special conditions:										
The design has been reviewed and upon completion should meet the regulations and requirements as noted on the application. The driveway shall be constructed per approved subdivision plans if applicable. For inspection of driveway associated with a building permit, call Lake County Building Services Division at 352-343-9634. In inspection of a joint (Common Split) driveway or a driveway not associated with a building permit, call Lake County Public Works Department at 352-253-6019. Submit permit to: Lake County Public Works, Post Office Box 781 Tavares, FL 32778										
Public Works Department Road Operations Division	7/13//8 Residential Driveway Apron Permit Effective February 2017									

JAN 25 2019



## Residential Driveway Apron Permit Application Requirements

Ш												
	To be completed by County Staff											***
		Single Family Driveway (standard A) Joint Driveway (Common/Split) (standard B)	C.	-		Ø mit			9 é		8.4	
		Driveway apron as Swale Check (standard C) Piped Driveway apron (standard D) Driveway apron conforming to Grade or Swale (standard E)						, ,				
		Driveway apron with Miami Curb & Gutter (standard M) Driveway apron with Standard Curb & Gutter (standard S)										
	*The	applicable driveway apron standard will be included with an	perj	mlt	.tha	at is	<i>ŝ</i> e	nt t	'O Er	nlia	maste '	
	1.	Sidewalks must be constructed per FDOT Index 310, with maximum thickness (See data)	m c	ros	88	ODE		4 1			3116+ ·	

- minimum thickness, (See detail on attachment).
- To conform to sidewalk requirements, subdivision construction plans are available for review in the 2, Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
- Drīveways are not permitted in the radius return of an intersection. With the exception of joint 3. driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10 feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4 foot wide flares on either side of the driveway, for a maximum width of 32' at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
- Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If paver's are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
- If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If 5. there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of mitter to the end of mitter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
- Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compilance with ADA requirements.
- 7. Driveway permit shall expire one (1) year from date approved.
- Driveway Apron Permit Application shall include a check made payable to the Lake County Board of 8.

I have read and understand the above requirements

Public Works Department Road Operations Division

Applicant's Signature/Date

Residential Driveway Apron Permit Effective February 2017