

<u>cjbhowes@aol.com</u> Applicant's e-mail address

Road Operations Division

Residential Driveway Apron Permit Application (Please Print or Type)

Contractor License # (Required unless built by owner)

Effective February 2017

Bldg Permit No. Date: Carl Ludecke - Charlie Johnson Bulber 36737431 Applicant/ Name Permit Will Be Returned To: Alt. Key# 40710 Thomas Boat Landing 18650 Huy 441 Applicant's Street Address House Number / Road Name Mt-Dora FL 3275 Applicant's City, State, Zip Subdivision Name Car | Ludecke Applicant, Please Print Name 383-6104 Signature of Applicant CBCO21054

A driveway permit is required to construct a new driveway, modify an existing driveway to meet county requirements, or install a temporary construction entrance within the public rights-of-way of County maintained roads. Issuance of a driveway permit does not vest any rights to the property owner for zoning, land use changes, or site improvements. The owner must follow all County procedures for permitting.

Driveway must be constructed in accordance with the Lake County Land Development Regulations and as shown on the attached sketch. Applicant holds Lake County harmless from all damages, claims, or injuries which may result from such work. Any deviation from the attached sketch must first be approved in writing by Lake County Public Works Department. Please see attached minimum requirement details for specifications.

Clay Road - No apron required - culvert pipe may be required - sod all disturbed areas.

Paved Road - Option 1: 6" limerock base and minimum 1" Type S-III Asphalt. Option 2: 6"reinforced concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of existing pavement. Culvert pipe may be required - Sod all disturbed areas.

In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.

County Road # 7940 To be completed I	by County Staf	f	
Driveway Permit Fee: \$50.00 Check/Transaction #: 52.72	24/ Date:	2/15/18	Fee Code: PUBSV1
Permit # 15882 Maint Area: 3 Signed:			Date Approved:
Permit Shall Expire One (1) Year From Date Approved	Date Expired:		
Date of Final Inspection: Inspector:		erengana e tyler - tyl	
Comments or special conditions:			
The design has been reviewed and upon completion should application. The driveway shall be constructed per approved driveway associated with a building permit, call Lake Conspection of a joint (Common Split) driveway or a driveway Public Works Department at 352-253-6019. Submit permit Tavares, FL 32778	yed subdivision ounty Building y not associated	plans if a Services E with a buil	pplicable. For inspection of a Division at 352-343-9634. For ding permit, call Lake County
Public Works Department	7/13/18	Reside	ential Driveway Apron Permit



Residential Driveway Apron Permit Application Requirements

, and the state of												
	To be completed by County Staff											
	Single Family Driveway (chandard a)	9		d)	8		4	4	9	Za.	Q	
	Joint Driveway (Common/Split) (standard B)	(Hzz)		.,		-					<i>C</i> .	
	· ·	Permit Number										
	Driveway apron as Swale Check (standard C)											
Li riped Driveway abron (standard b)												
	Driveway apron conforming to Grade or Swale (standard E)											
	Driveway apron with Miami Curb & Gutter (standard M)											
	Driveway apron with Standard Curb & Gutter (standard S)											
*The product (standard 5)												
*The applicable driveway apron standard will be included with approved permit that is sent to applicant. *												
1	Cidowallo	****		LI IC	44 15	30	1117	ט כ	īNĎ	uca	<u>nc. *</u>	
т.	Sidewalks must be constructed per FDOT Index 310, with maximum	~~~~~	rac				4 1	~^^	-		Control of the Contro	

- Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment).
- To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
- 3. Driveways are not permitted in the radius return of an intersection. With the exception of joint driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10 feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4 foot wide flares on either side of the driveway, for a maximum width of 32' at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
- 4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
- 5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in All right-of-way must be restored to its original condition and in accordance to applicable Lake responsible for sod until it is established.
- 6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway slope) in compliance with ADA requirements.
- 7. Driveway permit shall expire one (1) year from date approved.
- 8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements

Applicant's Signature/Date

Public Works Department Road Operations Division

Residential Driveway Apron Permit Effective February 2017