Effective February 2017



## Residential Driveway Apron Permit Application (Please Print or Type)

LAKE COUNTY
PUBLIC WORKS DEPARTMENT

	Date: 1-18-18 Bldg Permit No.	disconstructive and secundarity and secundarit	
	Ayex Homes LLC Applicant/ Name Permit Will Be Returned To:	3853521 / 29 / 18 / 26 Alt. Key# Section Township Range	
	28 E Washington St. Applicant's Street Address	37101 Scenic Bluff Dr. House Number / Road Name	
	Orlando FL 32801 Applicant's City, 80 te, 71p	Windy Ridge / 71 Subdivision Name	
	Signature of Applicant Phone Number	Jeffery L. Huebner Applicant, Please Print Name	
	TEFFE AVEXNOMES.COM Applicant's e-mail address	CBC05789 W Contractor License # (Required unless built by owner)	
	install a temporary construction entrance within the public	ay, modify an existing driveway to meet county requirements, or rights-of-way of County maintained roads. Issuance of a driveway zoning, land use changes, or site improvements. The owner must	
	attached sketch. Applicant holds Lake County harmless f	be constructed in accordance with the Lake County Land Development Regulations and as shown on the h. Applicant holds Lake County harmless from all damages, claims, or injuries which may result from such viation from the attached sketch must first be approved in writing by Lake County Public Works Department, ched minimum requirement details for specifications.	
Clay Road — No apron required — culvert pipe may be required — sod all disturbed areas.  Paved Road — Option 1: 6" limerock base and minimum 1" Type S-III Asphalt. Option 2: 6"r concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of 6" wire mesh placed a minimum of 10' from edge of the concrete (3000 PSI) using 10 foot square of		minimum 1" Type S-III Asphalt. Option 2: 6"reinforced	

In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.

payement. Culvert pipe may be required - Sod all disturbed areas.

Road Operations Division

County Road # 674BA To be completed by County Staff
Driveway Permit Fee: \$50.00 Check/Transaction #: 526423 Date: 1/1/18 Fee Code: PUBSV1
Permit#15896
Permit Shall Expire One (1) Year From Date Approved Date Expired:
Date of Final Inspection: Inspector:
Comments or special conditions:
The design has been reviewed and upon completion should meet the regulations and requirements as noted on this application. The driveway shall be constructed per approved subdivision plans if applicable. For inspection of a driveway associated with a building permit, call Lake County Building Services Division at 352-343-9634. For inspection of a joint (Common Split) driveway or a driveway not associated with a building permit, call Lake County Public Works Department at 352-253-6019. Submit permit to: Lake County Public Works, Post Office Box 7800, Tavares, FL 32778
Public Works Department Data One 7/3/18 Residential Driveway Apron Permit



## Residential Driveway Apron Permit Application Requirements

To be completed by County Staff		
Single Family Driveway (standard A)  Joint Driveway (Common/Split) (standard B)	Permit Number	
<ul> <li>Driveway apron as Swale Check (standard C)</li> <li>Piped Driveway apron (standard D)</li> <li>Driveway apron conforming to Grade or Swale (standard E)</li> </ul>		
☐ Driveway apron with Miami Curb & Gutter (standard M)☐ Driveway apron with Standard Curb & Gutter (standard S)	the state of the s	
*The applicable driveway apron standard will be included with approved permit that is sent to applicant. *		

- 1. Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment).
- 2. To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
- Driveways are not permitted in the radius return of an intersection. With the exception of joint driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10 feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4 foot wide flares on either side of the driveway, for a maximum width of 32' at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
- 4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
- 5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
- 6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
- 7. Driveway permit shall expire one (1) year from date approved.

8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements

Applicant's Signature/Date

Residential Driveway Apron Permit Effective February 2017

Public Works Department Road Operations Division