




**Residential Driveway Apron
Permit Application**
(Please Print or Type)



Date: 3-5-18

Bldg Permit No. 201701092

Brent Rigby

Applicant/ Name Permit Will Be Returned To:

16362 SE 81st Ter

Applicant's Street Address

Summersville, FL 32491

Applicant's City, State, Zip

Brent Rigby 951-314-4556

Signature of Applicant

Phone Number

BRENTDRIGBY@AOL.COM

Applicant's e-mail address

1483352 16 18 24

Alt. Key#

Section

Township

Range

922 Aisha Way

House Number / Road Name

Orange Blossom Gardens Unit 2

Subdivision Name

Brent Rigby

Applicant, Please Print Name

C4C1517353

Contractor License # (Required unless built by owner)

A driveway permit is required to construct a new driveway, modify an existing driveway to meet county requirements, or install a temporary construction entrance within the public rights-of-way of County maintained roads. Issuance of a driveway permit does not vest any rights to the property owner for zoning, land use changes, or site improvements. The owner must follow all County procedures for permitting.

Driveway must be constructed in accordance with the Lake County Land Development Regulations and as shown on the attached sketch. Applicant holds Lake County harmless from all damages, claims, or injuries which may result from such work. Any deviation from the attached sketch must first be approved in writing by Lake County Public Works Department. Please see attached minimum requirement details for specifications.

Check one:

☐ Clay Road – No apron required – culvert pipe may be required – sod all disturbed areas.

☒ Paved Road – Option 1: 6" limerock base and minimum 1" Type S-III Asphalt. Option 2: 6" reinforced concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of existing pavement. Culvert pipe may be required – Sod all disturbed areas.

In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.

County Road # 7901

To be completed by County Staff

Driveway Permit Fee: \$50.00 Check/Transaction #: 531275 Date: 3/29/18 Fee Code: PUBSV1

Permit # 15937 Maint Area: 1 Signed: _____ Date Approved: _____

Permit Shall Expire One (1) Year From Date Approved Date Expired: _____

Date of Final Inspection: _____ Inspector: _____

Comments or special conditions: _____

The design has been reviewed and upon completion should meet the regulations and requirements as noted on this application. The driveway shall be constructed per approved subdivision plans if applicable. For inspection, call Lake County Building Services Division at 352-343-9634. For joint (Common Split) driveway inspection, call Lake County Public Works Department at 352-253-6019.

Submit permit to: *Lake County Public Works, Post Office Box 7800, Tavares, FL 32778*

Public Works Department
Road Operations Division

_____ 7/13/18
_____ 7/13/18
_____ 7/13/18
_____ 7/13/18
_____ 7/13/18
_____ 7/13/18

Residential Driveway Apron Permit
Effective June 2015



Residential Driveway Apron Permit Application Requirements

To be completed by County Staff

- ☐ Single Family Driveway (standard A)
- ☐ Joint Driveway (Common/Split) (standard B)
- ☐ Driveway apron as Swale Check (standard C)
- ☐ Piped Driveway apron (standard D)
- ☐ Driveway apron conforming to Grade or Swale (standard E)
- ☐ Driveway apron with Miami Curb & Gutter (standard M)
- ☐ Driveway apron with Standard Curb & Gutter (standard S)

2017101092
Permit Number

*The applicable driveway apron standard will be included with approved permit that is sent to applicant. *

1. Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment).
2. To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
3. Driveways are not permitted in the radius return of an intersection. Driveway aprons must be 100 feet from the nearest intersecting road and may not exceed 24 feet in width at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
7. Driveway permit shall expire one (1) year from date approved.
8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements


Applicant's Signature/Date