



## Residential Driveway Apron Permit Application

LAKE CO
THE PARTIES AND
or my to missing white the contract
Range /
Nainge /
, LOT 3
· · · · · · · · · · · · · · · · · · ·
ouilt by owner)
•
equirements, or te of a driveway The owner must
s shown on the esult from such ks Department.
: 6"reinforced
ge of existing
ar hats
n traversing the
n traversing the
n traversing the
/** /** //\$
ode: PUBSV1
/** /** //\$
ode: PUBŠV1
ode: PUBŠV1
ode: PUBŠV1
ode: PUBŠV1
ode: PUBSV1
as noted on this section, call Lake
ode: PUBSV1 ed: as noted on this
as noted on this section, call Lake call Lake County
ode: PUBSV1  ed: as noted on this section, call Lake County
as noted on this section, call Lake call Lake County

'urned \*o Client



## Residential Driveway Apron Permit Application Requirements

To be completed by County Staff			
曾	Single Family Driveway (standard A) Joint Driveway (Common/Split) (stand	ard B) Permit Number	
	Driveway apron as Swale Check (standa Piped Driveway apron (standard D) Driveway apron conforming to Grade or		
	Driveway apron with Miami Curb & Gut Driveway apron with Standard Curb & C		
*The	e applicable driveway apron standard will be in	icluded with approved permit that is sent to applicant. *	
1.	Sidewalks must be constructed per FDOT In minimum thickness. (See detail on attachme	dex 310, with maximum cross slope of 1.5%, 6 inches nt).	
2,	To conform to sidewalk requirements, subc Lake County Public Works Department locat	livision construction plans are available for review in the ed at 437 Ardice Avenue in Eustis.	
3.	feet from the nearest intersecting road an	return of an intersection. Driveway aprons must be 100 in may not exceed 24 feet in width at the edge of the nitted to the Lake County Public Works Department.	
4.	repair. If pavers are removed to facilitate	the resident's responsibility to maintain, replace and/or Lake County and/or a utility company to perform utility s) used as replacements may not be able to be matched.	
5.	there are no other culverts in the neighborh diameter and a minimum of 30 feet in leng All right-of-way must be restored to its o	same diameter of existing culverts in neighborhood. If tood, the culvert pipe shall be a minimum of 15 inches in the measured from the end of miter to the end of miter. The signal condition and in accordance to applicable take sodded, matching existing grass type. Applicant shall be	
6.	County Public Works Department. In area	%. Variance requests should be submitted to the Lake s where sidewalks are present or planned, the driveway raversing the driveway apron (at a maximum 1.5% cross s.	
7.	Driveway permit shall expire one (1) year fr	om date approved.	,
8.	Driveway Apron Permit Application shall ind County Commissioners (BOCC).	ude a check made payable to the Lake County Beard of	///
I have read and understand the above requirements Applicant's Signature/Date			
	Public Works Department Road Operations Division	Residential Driveway Aprou Permit Effective February 2015	