

Residential Driveway Apron Permit Application

	Print or Type)	MAY 2 1 2018	
Date: May 11, 2018 Bldg Permit No. 20	18050941	I. AKE CHADATAY Perlawata desambi	
Jennifer Murphy	3818516 ,27	,21 ,26	
Applicant/ Name Permit Will Be Returned To:	Alt. Key# Section	Township Range	
10027 Tween Waters Street	BRIDGES GLEN S	UBLOT 5 15/41 Branchok	
Applicant's Street Address	House Number / Road Name		
Clermont, FL 34715	Bridges Glen	1	
Applicant's City, State, Zip	Subdivision Name		
Jeruin Muy 352-536-4481	Jennifer Murphy	j	
Signature of Applicant Phone Number	Applicant, Please Print Nam	e	
jennifer@alpha-inspections.net	Owner Builder		
Applicant's e-mail address	Contractor License # (Requ	ired unless built by owner)	
Install a temporary construction entrance within the public rights-of-way of County maintained roads. Issuance of a driveway permit does not vest any rights to the property owner for follow all County procedures for permitting. Driveway must be constructed in accordance with the Lake County Land Development Regulations and as shown on the attached sketch. Applicant holds Lake County harmless from all damages, claims, or injuries which may result from such work. Any deviation from the attached sketch must first Please see attached minimum requirement details for specifications. Check one: Clay Road — No apron required — culvert pipe may be required — sod all disturbed areas. Paved Road — Option 1: 6" limerock base and minimum 1" Type S-III Asphalt. Option 2: 6"reinforced concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of existing pavement. Culvert pipe may be required — Sod all disturbed areas. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.			
County Road # 2254B To be completed by County Staff			
Driveway Permit Fee: \$50.00 Check/Transaction #:	539134 Date: 6/19/18	Fee Code: PUBSV1	
Permit # 15470 Maint Area: 2 Sig	gned:	Date Approved:	
Permit Shall Expire One (1) Year From Date Approved Date Expired:			
Date of Final Inspection: Inspector:			
Comments or special conditions:		111	
· · · · · · · · · · · · · · · · · · ·			

The design has been reviewed and upon completion should meet the regulations and requirements as noted on this application. The driveway shall be constructed per approved subdivision plans if applicable. For inspection of a driveway associated with a building permit, call Lake County Building Services Division at 352-343-9634. For inspection of a joint (Common Split) driveway or a driveway not associated with a building permit, call Lake County Public Works Department at 352-253-6019. Submit permit to: Lake County Public Works, Post Office Box 7800, Tavares, FL 32778

Public Works Department Road Operations Division

red Data One 7/3

Residential Driveway Apron Permit Effective February 2017



Residential Driveway Apron Permit Application Requirements

PLORIBA CHITTE Application requirements			
To be completed by County Staff			
☐ Single Family Driveway (standard A)☐ Joint Driveway (Common/Split) (standa	rd B) Permit Number		
 Driveway apron as Swale Check (standar Piped Driveway apron (standard D) Driveway apron conforming to Grade or S 			
Driveway apron with Miami Curb & GutteDriveway apron with Standard Curb & G			
*The applicable driveway apron standard will be inc	luded with approved permit that is sent to applicant. *		
Sidewalks must be constructed per FDOT Ind minimum thickness. (See detail on attachmen	ex 310, with maximum cross slope of 1.5%, 6 inches t).		

- 2. To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
- 3. Driveways are not permitted in the radius return of an intersection. With the exception of joint driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10 feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4 foot wide flares on either side of the driveway, for a maximum width of 32' at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
- 4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
- 5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
- 6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
- 7. Driveway permit shall expire one (1) year from date approved.

8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements

Public Works Department Road Operations Division Applicant's Signature/Date

Residential Driveway Apron Permit Effective February 2017