

Residential Driveway Apron Permit Application (Please Print or Type)

Bldg Permit **3.0 1 8 0 5 0 4 3** 6

MAY 89 2018

Jeffrey Hedges	/ 29 / 19 / 25
Applicant/ Name Permit Will Be Returned To:	Alt. Key# Section Township Range
4401 Vineland Rd Suite A-11	31517 Broadwater Avenue
Applicant's Street Address	House Number / Road Name
Orlando FL 32811	Park Hill Phase II
Applicant's City, State, Zip	Subdivision Name
1 Halo 407-523-1030	_Jeffrey Hedges
Signature of Applicant Phone Number	Applicant, Please Print Name
orlandowarranty@adamshomes.com	_CRC1330146
Applicant's e-mail address	Contractor License # (Required unless built by owner)
install a temporary construction entrance within the public permit does not vest any rights to the property owner for follow all County procedures for permitting. Driveway must be constructed in accordance with the La attached sketch. Applicant holds Lake County harmless for permitting.	y be required — sod all disturbed areas. minimum 1" Type S-III Asphalt. Option 2: 6"reinforced
∑ Paved Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required — Sod all did in areas where sidewalks are present or planned, the dr driveway apron (at a maximum 1.5% cross slope) in complete.	iveway must include a minimum 4 foot wide path traversing the lance with ADA requirements.
☐ Paved Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required — Sod all did In areas where sidewalks are present or planned, the dr driveway apron (at a maximum 1.5% cross slope) in complete County Road #	sturbed areas. iveway must include a minimum 4 foot wide path traversing the lance with ADA requirements. ileted by County Staff
∑ Paved Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required — Sod all did in areas where sidewalks are present or planned, the dr driveway apron (at a maximum 1.5% cross slope) in complete.	sturbed areas. iveway must include a minimum 4 foot wide path traversing the lance with ADA requirements. ileted by County Staff
Name	sturbed areas. iveway must include a minimum 4 foot wide path traversing the lance with ADA requirements. ileted by County Staff
Name	iveway must include a minimum 4 foot wide path traversing the lance with ADA requirements. Ileted by County Staff Fee Code: PUBSV1 Inde: Date Approved:
Paved Road - Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required - Sod all did in areas where sidewalks are present or planned, the driveway apron (at a maximum 1.5% cross slope) in complete County Road # 49296 To be complete Driveway Permit Fee: \$50.00 Check/Transaction #: Signature Sig	iveway must include a minimum 4 foot wide path traversing the lance with ADA requirements. Ideted by County Staff Fee Code: PUBSV1 Ined: Date Approved:
Name	iveway must include a minimum 4 foot wide path traversing the lance with ADA requirements. Ideted by County Staff Fee Code: PUBSV1 Ined: Date Approved:
Name Paved Road - Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required - Sod all did in areas where sidewalks are present or planned, the driveway apron (at a maximum 1.5% cross slope) in complete	iveway must include a minimum 4 foot wide path traversing the lance with ADA requirements. Ideted by County Staff Fee Code: PUBSV1 Ined: Date Approved:
Paved Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required — Sod all did In areas where sidewalks are present or planned, the driveway apron (at a maximum 1.5% cross slope) in completion with the complete county Road # 4974	iveway must include a minimum 4 foot wide path traversing the lance with ADA requirements. Ideted by County Staff Fee Code: PUBSV1 Ined: Date Approved:
Paved Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required — Sod all did In areas where sidewalks are present or planned, the driveway apron (at a maximum 1.5% cross slope) in completion with the completion of a joint (Common Split) driveway or a driveway associated with a building permit, call La inspection of a joint (Common Split) driveway or a driveway, FL 32778	iveway must include a minimum 4 foot wide path traversing the lance with ADA requirements. Ideted by County Staff 39407 Date:
Paved Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required — Sod all did In areas where sidewalks are present or planned, the driveway apron (at a maximum 1.5% cross slope) in completion with the completion of a joint (Common Split) driveway or a driveway associated with a building permit, call La inspection of a joint (Common Split) driveway or a driveway, FL 32778 Public Works Department	iveway must include a minimum 4 foot wide path traversing the lance with ADA requirements. Ileted by County Staff Date: 6/4/8 Fee Code: PUBSV1 Ined: Date Approved: Date Expired: Should meet the regulations and requirements as noted on this approved subdivision plans if applicable. For inspection of a lake County Building Services Division at 352-343-9634. For iveway not associated with a building permit, call Lake County
Paved Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required — Sod all did In areas where sidewalks are present or planned, the driveway apron (at a maximum 1.5% cross slope) in completion with the completion of a joint (Common Split) driveway or a driveway associated with a building permit, call La inspection of a joint (Common Split) driveway or a driveway, FL 32778 Public Works Department	iveway must include a minimum 4 foot wide path traversing the lance with ADA requirements. Ideted by County Staff 39407 Date: b/Uffe Fee Code: PUBSV1



Residential Driveway Apron Permit Application Requirements

12		<u> </u>
: 2. ² ,	To be completed by County Staff 2	18050436
	Single Family Driveway (standard A)	그 강 강 [문장] - 그 그는 것 뭐
		Permit Number
X	Driveway apron as Swale Check (standard C) Piped Driveway apron (standard D)	
	Driveway apron conforming to Grade or Swale (standard E)	
i i.i.		li ira 14 lii
	Driveway apron with Miami Curb & Gutter (standard M) Driveway apron with Standard Curb & Gutter (standard S)	
<u>*Th</u>	ne applicable driveway apron standard will be included with approved permi	t that is sent to applicant. *
.1.	Sidewalks must be constructed per FDOT Index 310, with maximum cro	ss slope of 1.5%, 6 inches

- minimum thickness. (See detail on attachmen
- To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
- Driveways are not permitted in the radius return of an intersection. With the exception of joint driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10 feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4 foot wide flares on either side of the driveway, for a maximum width of 32 at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
- Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
- If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
- Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1,5% cross : slope) in compliance with ADA requirements.
- Driveway permit shall expire one (1) year from date approved.

Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements.

Applicant's Signature / Date

Residential Driveway Apron Permit Effective February 2017

Public Works Department Road Operations Division