

Residential Driveway Apron Permit Application (Please Print or Type)

	rint or Type)
Date: Bldg Permit No	30700
Cor Ludecke Applicant/ Name Permit Will Be Returned To:	3836291, 23 , 18 , 27 Alt. Key# Section Township Range
18650 US Hwy 441 Applicant's Street Address	22180 Deer Pouk Ave House Number / Road Name
Mt-Dora, FL 32757 Applicant's City, State, Zip	Doer Park Subdivision Name
Signature of Applicant Phone Number	Applicant, Please Print Name
cjb howes @ aol.com Applicant's e-mail address	CBCD21054 Contractor License # (Required unless built by owner)
install a temporary construction entrance within the public ri	y, modify an existing driveway to meet county requirements, or ights-of-way of County maintained roads. Issuance of a driveway oning, land use changes, or site improvements. The owner must
attached sketch. Applicant holds Lake County harmless fr work. Any deviation from the attached sketch must first be Please see attached minimum requirement details for specific Check one: Clay Road — No apron required — culvert pipe may Paved Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required — Sod all distances where sidewalks are present or planned, the drivers with the square of the same present or planned, the drivers with the same present or planned.	y be required — sod all disturbed areas. minimum 1" Type S-III Asphalt. Option 2: 6"reinforced wire mesh placed a minimum of 10' from edge of existing sturbed areas. veway must include a minimum 4 foot wide path traversing the
driveway apron (at a maximum 1.5% cross slope) in complia County Road # 7483/4 To be complete	eted by County Staff
	/ /
	S39433 Date: 6/2//8 Fee Code: PUBSV1 Date: Approved:
Permit Shall Expire One (1) Year From Date Approved	
Date of Final Inspection: Inspec	
Comments or special conditions:	
application. The driveway shall be constructed per a driveway associated with a building permit, call La inspection of a joint (Common Split) driveway or a	hould meet the regulations and requirements as noted on this approved subdivision plans if applicable. For inspection of a tke County Building Services Division at 352-343-9634. For iveway not associated with a building permit, call Lake County permit to: Lake County Public Works, Post Office Box 7800,
Public Works Department Road Operations Division Entered Data One	Residential Driveway Apron Permit Effective February 2017

Entered Data One	7/04/0
st Scan	7/13/18
odated Data One	
econd Scan	•
turned to Client	



MAY 9 5 2018

Residential Driveway Apron Permit Application Requirements

Tolon		-			_								
To be completed by County Staff	•												
Single Family Driveway (standard A)	2	n	1	Q	n		A	7	0	Λ			
Joint Driveway (Common/Split) (standard B)	1344E	49		<u> </u>	V		V	4	w	U			
(standard B)				Permit Number									
 Driveway apron as Swale Check (standard C) Piped Driveway apron (standard D) Driveway apron conforming to Grade or Swale (standard E))												
 Driveway apron with Miami Curb & Gutter (standard M) Driveway apron with Standard Curb & Gutter (standard S) 													
*The applicable driveway apron standard will be included with approved	pe	rmi	t th	<u>at i</u>	is s	<u>ent</u>	: to	apr	olica	ant. *			
1. Sidewalks must be constructed and Thomas						-							

- Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment).
- To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
- 3. Driveways are not permitted in the radius return of an intersection. With the exception of joint driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10 feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4 foot wide flares on either side of the driveway, for a maximum width of 32' at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
- 4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
- 5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
- 6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
- Driveway permit shall expire one (1) year from date approved.
- 8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements

Applicant's Signature/Date

Public Works Department Road Operations Division

Residential Driveway Apron Permit Effective February 2017