

## Residential Driveway Apron Permit Application (Please Print or Type)

2018051113

MAY 2 4 2018

Date: 217170 Bidg Permit No.	LPUBLIC WOLLD DO NOT A LAND
Kenneth Smith	3907876 / 13 / 24 / 26
Applicant/ Name Permit Will Be Returned To:	Alt. Key# Section Township Range
4901 Vineland Road	17320 Bracken Fern Land
Applicant's Street Address	House Number / Road Name
Orlando, FL 32811	SERENOA /L+ 336
Applicant's City, State, Zip	Subdivision Name
huttur 407-661-2161	Kenneth Smith
Signature of Applicant Phone Number	Applicant, Please Print Name
NFLPermitting@Pulte.com	CGC 1520694
Applicant's e-mail address	Contractor License # (Required unless built by owner)
install a temporary construction entrance within the public permit does not vest any rights to the property owner for follow all County procedures for permitting.  Driveway must be constructed in accordance with the L	ray, modify an existing driveway to meet county requirements, or rights-of-way of County maintained roads. Issuance of a driveway zoning, land use changes, or site improvements. The owner must ake County Land Development Regulations and as shown on the
attached sketch. Applicant holds Lake County harmless	from all damages, claims, or injuries which may result from such be approved in writing by Lake County Public Works Department.
Check one:	
☐ Clay Road — No apron required — culvert pipe m ☐ Paved Road — Option 1: 6" limerock base and	minimum 1" Type S-III Asphalt. Option 2: 6"reinforced
concrete (3000 PSI) using 10 foot square of 6" x 6 pavement. Culvert pipe may be required — Sod all d	
pavement. Culvert pipe may be required — Sod all d	isturbed areas.
pavement. Culvert pipe may be required — Sod all d	isturbed areas.  riveway must include a minimum 4 foot wide path traversing the
In areas where sidewalks are present or planned, the didriveway apron (at a maximum 1.5% cross slope) in comp	isturbed areas.  riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.
In areas where sidewalks are present or planned, the didriveway apron (at a maximum 1.5% cross slope) in comp  County Road #	isturbed areas.  riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  pleted by County Staff
In areas where sidewalks are present or planned, the didriveway apron (at a maximum 1.5% cross slope) in comp  County Road # 5266 To be comp	isturbed areas.  riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.
In areas where sidewalks are present or planned, the didriveway apron (at a maximum 1.5% cross slope) in comp  County Road #	riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.    Detect   Detect
In areas where sidewalks are present or planned, the didriveway apron (at a maximum 1.5% cross slope) in comp  County Road #	riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.    Detected by County Staff
In areas where sidewalks are present or planned, the didriveway apron (at a maximum 1.5% cross slope) in comp  County Road #	riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.    Description   Desc
In areas where sidewalks are present or planned, the didriveway apron (at a maximum 1.5% cross slope) in comp  County Road #	riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.    Description   Desc
In areas where sidewalks are present or planned, the didriveway apron (at a maximum 1.5% cross slope) in comp  County Road #	riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.    Description   Desc
In areas where sidewalks are present or planned, the didriveway apron (at a maximum 1.5% cross slope) in comp  County Road #	riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.    Description
In areas where sidewalks are present or planned, the didriveway apron (at a maximum 1.5% cross slope) in comp  County Road #	riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.    Detected by County Staff
In areas where sidewalks are present or planned, the didriveway apron (at a maximum 1.5% cross slope) in composition.  County Road #	riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.    Description   Description   Date   Date
In areas where sidewalks are present or planned, the divideway apron (at a maximum 1.5% cross slope) in comp  County Road #	riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.    Detected by County Staff
In areas where sidewalks are present or planned, the divideway apron (at a maximum 1.5% cross slope) in composition.  County Road #	riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.    Description   Date   Date
In areas where sidewalks are present or planned, the didriveway apron (at a maximum 1.5% cross slope) in composition.  County Road #	riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.    Description   Date   Date
In areas where sidewalks are present or planned, the divideway apron (at a maximum 1.5% cross slope) in composition.  County Road #	riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.    Deleted by County Staff



## Residential Driveway Apron Permit Application Requirements

To be completed by County Staff
☐ Single Family Driveway (standard A) 2018051113
☐ Joint Driveway (Common/Split) (standard B) Permit Number
Driveway apron as Swale Check (standard C)
Piped Driveway apron (standard D)
☐ Driveway apron conforming to Grade or Swale (standard E)
☐ Driveway apron with Miami Curb & Gutter (standard M)
Driveway apron with Standard Curb & Gutter (standard S)
*The applicable driveway apron standard will be included with approved permit that is sent to applicant. *
1. Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches
minimum thickness. (See detail on attachment).
2. To conform to sidewalk requirements, subdivision construction plans are available for review in the
Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
· · · · · · · · · · · · · · · · · · ·
3. Driveways are not permitted in the radius return of an intersection. With the exception of joint
driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10
feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4
foot wide flares on either side of the driveway, for a maximum width of 32' at the edge of the
roadway. Variance requests should be submitted to the Lake County Public Works Department.
为此,"我们就是我们的,我们就是我们的,我们就是我们的,我们就是我们的,我们就是我们的,我们就是我们的。""我们就是我们的,我们就是我们的,我们就是我们的,我们
4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or
repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
"我们是一个一个一直,我把自己的人,你也没有什么,你们一个事,没事的,你不知道的事,你不知道,我们就是一个一个
5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If
there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in
diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter.
All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be
responsible for sod until it is established.
经推销 医二氯化物 医皮肤 化二甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基
6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake
County Public Works Department. In areas where sidewalks are present or planned, the driveway
must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
7. Driveway permit shall expire one (1) year from date approved.
8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of
County Commissioners (BOCC).
I have read and understand the above requirements
Applicant's Signature/Date

Public Works Department Road Operations Division Residential Driveway Apron Permit
Effective February 2017