

Residential Driveway Apron Permit Application 2(Please Printer Type) 4 6

Eldg Permit No. MAY 0 9 2018

| Kenneth Smith | 3907852,13,24,26 |
|--|--|
| Applicant/ Name Permit Will Be Returned To: | Alt. Key# Section Township Range |
| 4901 Vineland Road | 17264 Golderest Losp |
| Applicant's Street Address | House Number / Road Name |
| Orlando, FL 32811 | SERENOA , Let 234 |
| Applicant's City,/State, Zip | Subdivision Name |
| Secretary 407-661-2161 | Kenneth Smith |
| Signature of Applicant Phone Number | Applicant, Please Print Name |
| NFLPermitting@Pulte.com | CGC 1520694 |
| Applicant's e-mail address | Contractor License # (Required unless built by owner) |
| install a temporary construction entrance within the public | way, modify an existing driveway to meet county requirements, or crights-of-way of County maintained roads. Issuance of a driveway r zoning, land use changes, or site improvements. The owner must |
| attached sketch. Applicant holds Lake County harmless | Lake County Land Development Regulations and as shown on the from all damages, claims, or injuries which may result from such the approved in writing by Lake County Public Works Department. |
| ▼ Paved Road - Option 1: 6" limerock base and | nay be required — sod all disturbed areas. d minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 6" wire mesh placed a minimum of 10' from edge of existing |
| | hay be required — sod all disturbed areas. d minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 6" wire mesh placed a minimum of 10' from edge of existing disturbed areas. driveway must include a minimum 4 foot wide path traversing the bliance with ADA requirements. |
| | hay be required — sod all disturbed areas. d minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 6" wire mesh placed a minimum of 10' from edge of existing disturbed areas. driveway must include a minimum 4 foot wide path traversing the bliance with ADA requirements. |
| | hay be required — sod all disturbed areas. d minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 6" wire mesh placed a minimum of 10' from edge of existing disturbed areas. driveway must include a minimum 4 foot wide path traversing the bliance with ADA requirements. |
| Permit # 15978 Maint Area: Si | hay be required — sod all disturbed areas. d minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 5" wire mesh placed a minimum of 10' from edge of existing disturbed areas. driveway must include a minimum 4 foot wide path traversing the pliance with ADA requirements. Determine the place of existing disturbed areas. |
| Paved Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6 pavement. Culvert pipe may be required — Sod all d In areas where sidewalks are present or planned, the d driveway apron (at a maximum 1.5% cross slope) in comp County Road # 6264 To be com Driveway Permit Fee: \$50.00 Check/Transaction #: | hay be required — sod all disturbed areas. d minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 5" wire mesh placed a minimum of 10' from edge of existing disturbed areas. driveway must include a minimum 4 foot wide path traversing the pliance with ADA requirements. Determine the place of existing disturbed areas. |
| Permit # 15978 Maint Area: Si | nay be required - sod all disturbed areas. d minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 5" wire mesh placed a minimum of 10' from edge of existing disturbed areas. driveway must include a minimum 4 foot wide path traversing the pliance with ADA requirements. Determine the county Staff Signal: Date: 6/2 2/22 Date Approved: Date Expired: |
| Paved Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6 pavement. Culvert pipe may be required — Sod all do In areas where sidewalks are present or planned, the doriveway apron (at a maximum 1.5% cross slope) in composition of the compositi | hay be required - sod all disturbed areas. d minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 5" wire mesh placed a minimum of 10' from edge of existing disturbed areas. driveway must include a minimum 4 foot wide path traversing the plant by the color with ADA requirements. Determine the color of the color o |
| Paved Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6 pavement. Culvert pipe may be required — Sod all do In areas where sidewalks are present or planned, the doriveway apron (at a maximum 1.5% cross slope) in composition. To be composition of a joint (Common Split) driveway or a doriveway of a final Inspection of a joint (Common Split) driveway or a doriveway or a dorive and sugar and suga | hay be required - sod all disturbed areas. d minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 5" wire mesh placed a minimum of 10' from edge of existing disturbed areas. driveway must include a minimum 4 foot wide path traversing the plant by the color with ADA requirements. Determine the color of the color o |
| Paved Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6 pavement. Culvert pipe may be required — Sod all d In areas where sidewalks are present or planned, the d driveway apron (at a maximum 1.5% cross slope) in comp County Road # 0.64 To be com Driveway Permit Fee: \$50.00 Check/Transaction #: Permit # 15478 Maint Area: Si Permit Shall Expire One (1) Year From Date Approve Date of Final Inspection: Inspection application. The driveway shall be constructed per driveway associated with a building permit, call I inspection of a joint (Common Split) driveway or a d Public Works Department at 352-253-6019. Submit | should meet the regulations and requirements as noted on this approved subdivision plans if applicable. For inspection of a Lake County Building Services Division at 352-343-9634. For Iriveway not associated with a building permit, call Lake County it permit to: Lake County Public Works, Post Office Box 7800, Residential Driveway Apron Permit Effective February 2017 |



Public Works Department Road Operations Division

Residential Driveway Apron Permit Application Requirements

| To be completed by County Staff |
|--|
| ☐ Single Family Driveway (standard A) ☐ Joint Driveway (Common/Split) (standard B) ☐ Permit Number |
| ☐ Driveway apron as Swale Check (standard C) ☐ Piped Driveway apron (standard D) ☐ Driveway apron conforming to Grade or Swale (standard E) |
| ☐ Driveway apron with Miami Curb & Gutter (standard M) ☐ Driveway apron with Standard Curb & Gutter (standard S) |
| *The applicable driveway apron standard will be included with approved permit that is sent to applicant. * |
| 1. Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment). |
| 2. To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares. |
| 3. Driveways are not permitted in the radius return of an intersection. With the exception of joint driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10 feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4 foot wide flares on either side of the driveway, for a maximum width of 32' at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department. |
| 4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched. |
| If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established. |
| 6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements. |
| 7. Driveway permit shall expire one (1) year from date approved. |
| 8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC). |
| I have read and understand the above requirements |

Residential Driveway Apron Permit Effective February 2017