

## Residential Driveway Apron Permit Application (Please Print or Type)

FLORIDA	PUBLIC V MAY 3 1 2018
Date: 5-23-18 Bldg Permit No	
Applicant/ Name Permit Will Be Returned To:	3853568 / 29 / 18 / 2.6 Alt. Key# Section Township Range
28 E Washington St. Applicant's Street Address	37050 Scenic Ridge Drive House Number / Road Name
Orlando FL 32801 Applicant's City, State, Appl	Subdivision Name
Signature of Applicant Phone Number	Jeffery L. Huebner Applicant, Please Print Name
Teffe avexhomes.com  Applicant's e-mail address	CBC05789 (Required unless built by owner)
install a temporary construction entrance within the public r	ry, modify an existing driveway to meet county requirements, or rights-of-way of County maintained roads. Issuance of a driveway zoning, land use changes, or site improvements. The owner must
attached sketch. Applicant holds Lake County harmless from the attached sketch must first be please see attached minimum requirement details for specific Check one:  Clay Road — No apron required — culvert pipe may Paved Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required — Sod all dispersions.	by be required — sod all disturbed areas.  minimum 1" Type S-III Asphalt. Option 2: 6"reinforced wire mesh placed a minimum of 10' from edge of existing sturbed areas.  Option 2: 6"reinforced wire mesh placed a minimum of 10' from edge of existing sturbed areas.
County Road # 6746C To be compl	leted by County Staff
Driveway Permit Fee: \$50.00 Check/Transaction #: 4	540 859 Date: 7/6//8 Fee Code: PUBSV1
Permit# 16000 Maint Area:   Sign	ned: Date Approved:
Permit Shall Expire One (1) Year From Date Approved	Date Expired:
Date of Final Inspection: Inspec	etor:
Comments or special conditions:	
application. The driveway shall be constructed per a driveway associated with a building permit, call La inspection of a joint (Common Split) driveway or a dri Public Works Department at 352-253-6019. Submit Tavares, FL 32778	hould meet the regulations and requirements as noted on this approved subdivision plans if applicable. For inspection of a like County Building Services Division at 352-343-9634. For iveway not associated with a building permit, call Lake County permit to: Lake County Public Works, Post Office Box 7800,
Public Works Department  Page Operations Division  St Scan	Residential Driveway Apron Permit  ### Effective February 2017

dated Data One \_ cond Scan urned to Client

Road Operations Division



## Residential Driveway Apron Permit Application Requirements

To be completed by Count  Single Family Driveway (standard A)  Joint Driveway (Common/Split) (standard B)	2018051429 Permit Number	
<ul> <li>□ Driveway apron as Swale Check (standard C)</li> <li>□ Piped Driveway apron (standard D)</li> <li>□ Driveway apron conforming to Grade or Swale (standard C)</li> </ul>	dard E)	
☐ Driveway apron with Miami Curb & Gutter (standard M) ☐ Driveway apron with Standard Curb & Gutter (standard S)		
*The applicable driveway apron standard will be included with approved permit that is sent to applicant. *		

- 1. Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment).
- 2. To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
- 3. Driveways are not permitted in the radius return of an intersection. With the exception of joint driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10 feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4 foot wide flares on either side of the driveway, for a maximum width of 32' at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
- 4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
- 5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
- 6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
- 7. Driveway permit shall expire one (1) year from date approved.

8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements

Applicant's signature/Date

Residential Driveway Apron Permit
Effective February 2017

Public Works Department Road Operations Division

