

Residential Driveway Apron Permit Application

(Please Print or Type)

MALLETAN	Chart	S. S	COUNTR	No Et	EUR!	20 14	W. A.	ijareno Gareno	i) Gans
Z	0	1	8	0	6	1	0	3	4

JUN 2 2 2018

8061034 Blda Permit No. 3907870 Kenneth Smith Applicant/ Name Permit Will Be Returned To: Alt. Kev# Range Golderes 4901 Vineland Road Applicant's Street Address House Number / Road Name /Lot 330 Orlando, FL 32811 SERENOA Applicant's City, State, Zip Subdivision Name Kenneth Smith 407-661-2161 Signature of Applicant Phone Number Applicant, Please Print Name NFLPermitting@Pulte.com CGC 1520694 Applicant's e-mail address Contractor License # (Required unless built by owner)

A driveway permit is required to construct a new driveway, modify an existing driveway to meet county requirements, or install a temporary construction entrance within the public rights-of-way of County maintained roads. Issuance of a driveway permit does not vest any rights to the property owner for zoning, land use changes, or site improvements. The owner must follow all County procedures for permitting.

Driveway must be constructed in accordance with the Lake County Land Development Regulations and as shown on the attached sketch. Applicant holds Lake County harmless from all damages, claims, or injuries which may result from such work. Any deviation from the attached sketch must first be approved in writing by Lake County Public Works Department. Please see attached minimum requirement details for specifications.

Check one:

☐ Clay Road - No apron required - culvert pipe may be required - sod all disturbed areas.

Paved Road - Option 1: 6" limerock base and minimum 1" Type S-III Asphalt. Option 2: 6"reinforced concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of existing pavement. Culvert pipe may be required - Sod all disturbed areas.

In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.

County Road #							
Driveway Permit Fee: \$50.00 Check/Transaction #: 54/233 Date: 7/11/18 Fee Code: PUBSV1							
Permit #							
Permit Shall Expire One (1) Year From Date Approved Date Expired:							
Date of Final Inspection: Inspector:							
Comments or special conditions:							
The design has been reviewed and upon completion should meet the regulations and requirements as noted on this application. The driveway shall be constructed per approved subdivision plans if applicable. For inspection of a driveway associated with a building permit, call Lake County Building Services Division at 352-343-9634. For inspection of a joint (Common Split) driveway or a driveway not associated with a building permit, call Lake County Public Works Department at 352-253-6019. Submit permit to: Lake County Public Works, Post Office Box 7800, Tavares, FL 32778							

Public Works Department Road Operations Division

re er Dats One	3/1/13
of Scan	3/1/8
dated Data One	
cond Scan	
med to Client	

Residential Driveway Apron Permit Effective February 2017



JUN 2 2 2018

Residential Driveway Apron Permit Application Requirements

To be completed by County Staff	2018061034					
☐ Single Family Driveway (standard A)☐ Joint Driveway (Common/Split) (standard B)						
	Permit Number					
☐ Driveway apron as Swale Check (standard C) ☐ Piped Driveway apron (standard D) ☐ Driveway apron conforming to Grade or Swale (standard E)						
 Driveway apron with Miami Curb & Gutter (standard M) Driveway apron with Standard Curb & Gutter (standard S) 						
*The applicable driveway apron standard will be included with approved permit that is sent to applicant. *						
1 Sidewalks must be constructed nor EDOT Index 210 with maximum						

- Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment).
- 2. To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
- 3. Driveways are not permitted in the radius return of an intersection. With the exception of joint driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10 feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4 foot wide flares on either side of the driveway, for a maximum width of 32' at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
- 4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
- 5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
- 6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
- 7. Driveway permit shall expire one (1) year from date approved.

8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements

Applicant's Signature/Date

Public Works Department Road Operations Division Residential Driveway Apron Permit Effective February 2017

PLOT PLAN 2018061034 DESCRIPTION:(AS FURNISHED) LOT 330, SERENOA VILLAGE 1 PHASE 1A-1 AS RECORDED IN PLAT BOOK 69, PAGE(S) 20-23, OF THE PUBLIC RECORDS OF LAKE COUNTY, FLORIDA. Funderstand that I have to meet all lot chapter 9 of the Land Development. Regulations, I also Development. Regulations, I also cartify that my Regulations, i also carmy that my development shall not advancely affect aurounding or downstream wetlands, floodplains or neighboring properties. Applicant Signature LOT 333 NOTICE TO OWNER AND CONTRACTOR The Assuance of a zoning clearance does not assure that the setbacks have been met or that the development does not encroach on an easement. The owners and/or the development does not encroach on an easement. The owners and/or clarified the sole responsibility of compilance with serbacks and no encroach responsibility of compilance with serbacks and no encroached the sole of the sole of the serbacks of restoring ease. I see mydrappy/sibility/NO graps bycotal parity/grass) can over more the serbacks of restoring ease. I see mydrappy/sibility/NO graps bycotal parity/grass) can over more the serbacks of restoring ease. I see that the serbacks of restoring ease the serbacks of restoring ease. I see that the serbacks of restoring ease the serbacks of restoring ease. I see that the serbacks of restoring ease. I see that the serbacks of restoring ease the serbac Line Tobie VOL Direction Length He1'29'31"E 50,00' Signature N61'29'31"E 50.00' i understand that I shall meet all Single-Family requirements as established in LDR 3.01.02(A; Residential Uses Classification of Uses. 3³ 701 S 400.95 PREPARED FOR: LEGEND: BUILDING SETBACK LINE ON LOT CALCULATIONS CENTERLINE S SQ. FT. **BUILDING SETBACKS** LOT LIVING AREA GARAGE = 6,250 = 2,162 = 402 RIGHT OF WAY LINE XXXX PROPOSED ELEVATION FRONT: 10 402 24 260 GARAGE: ENTRY \Longrightarrow PROPOSED DRAINAGE FLOW REAR: LANAI PATIO Secretary. CONCRETE SIDE: 0 328 AIR CONDITIONER SIDEWALK POINT OF INTERSECTION POINT OF CURVATURE POINT OF TANGENCY RADIUS POINT POINT OF COMPOUND CURVATURE POINT OF COMPOUND CURVATURE TYPICAL CONCRETE SLAB PER PLAT CALCULATED PLAT BOOK SIDE STREET: 10 DRIVEWAY A/C PAD WALKWAY IMPERVIOUS 328 9 38 52% 3223 3,027 NOTES: ELEVATIONS SHOWN ARE PER LOT GRADING PLANS PROVIDED BY THE CLIENT. ELEVATIONS ARE BASED ON NAVD 1988 DATUM. SQ. FT. OFF LOT CALCULATIONS RIGHT OF WAY DRIVE APRON PUBLIC S/W 550 114 250 SQ. FT. SQ. FT. SQ. FT. SQ. FT. THIS PLOT PLAN IS INTENDED FOR PERMITTING PURPOSES ONLY. THIS IS NOT INTENDED FOR THE CONSTRUCTION OF THE PROPOSED HOUSE, REFER TO HOUSE PLAN AND OPTION LIST FOR CONSTRUCTION. ALL BUILDING SET BACK LINES SHOWN HEREON IS PER DATA FURNISHED BY CLIENT AND IS FOR INFORMATIONAL PURPOSES ONLY. CALCULATED PLAT BOOK PAGES SOUARE FEET FEDERAL EMERGENCY MANAGEMENT AGENCY FLOOD INSURANCE RATE MAP NORTH AMERICAN VESTICAL DATUM NATIONAL GEODETIC VESTICAL DATUM DRAIMAGE & UTILITY DRAIMAGE & UTILITY DRAIMAGE ASSEMENT UTILITY EASEMENT SOD 186 TOTALS = 6,800 SQ. FT. AREA DRIVEWAY 442 SIDEWALK = 288 SQ. FT. THIS IS NOT A SURVEY SOD = 3,213SQ. FT. THIS IS A PLOT PLAN ONLY FLOOD NOTE: I HAVE EXAMINED THE F.I.R.M. MAP NO. 12069C0676F, OATED 12/48/2012, AND FOUND THE SUBJECT PROPERTY APPEARS TO LIE IN ZONE "X", AREAS DETERMINED TO BE OUTSIDE THE 0,2% ANNUAL CHANGE FLOODFLAIM, THE SURVEYOR MAKES NO SUBARANTEES AS TO THE ABOVE INFORMATION, PLEASE CONTACT THE LOCAL F.E.M.A. AGENT FOR VERIFICATION. SURVEYOR NOTES: 1. THE SURVEYOR HAS NOT ABSTRACTED THE LAND SHOWN HEREON FOR EASEMENTS, RIGHT OF WAY, RESTRICTIONS OF RECORD WHICH MAY AFFECT THE TITLE OF USE OF THE LAND. NO UNDERGROUND IMPROVEMENTS HAVE BEEN LOCATED EXCEPT AS SHOWN. BEARING BASIS: NOT VALID WITHOUT THE AUTHENTIC ELECTRONIC SIGNATURE AND THE AUTHENTIC ELECTRONIC SEAL OF A FLORIDA LICENSED SURVEYOR AND MAPPER. BEARINGS SHOWN HEREON ARE BASED ON THE CENTERLINE OF GOLDCREST LOOP BEING N61'29'31"E, PER PLAT, AMERICAN Surveying REVISED CIX. Digitally signed by Jim Boleman DN: C=US, O=American Surveying & Mepping, CN=Jim Boleman, E=Uboleman@asmcorporate;sgxr Location: Date: 2018-06-18 16:31:58 FiRM SCALE: 1" = 30 FEET &M APPING INC APPROVED BY: ___JB CERTIFICATION OF AUTHORIZATION NUMBER LB#6393 3191 MAGUIRE BOULEVARD, SUITE 200 ORLANDO, FLORIDA 32803 170503 LOT 330

(407) 426-7979 WWW.AMERICANSURVEYINGANDMAPPING.COM

JAMES W. BOLEMAN PSM# 6485

DRAWN BY;

PLOT PLAN 6/15/18 RMB