

## **Residential Driveway Apron Permit Application**

(Please Print or Type)

| JUN | 2 | 5 | 2018 |  |
|-----|---|---|------|--|
|     |   |   |      |  |

| FLORIDA  | The state of the s |
|--|--|
| Date: Bldg Permit No   |  |
| HOME DYNAMICS  | 3906/38,   |
| Name Permit Will Be Returned To:   | Alt. Key# Section Township Range   |
| 4755 TECHNOLOGY WAY #210   | 16844 MeAdows 5+   |
| Street Address   | House Number / Road Name   |
| BOCA RATON, JFL 33431  | GREATER LAKES LOT 35   |
| City, State, Zip (954)   | Subdivision Name   |
| 1800y 914-0246   | ISMAEL GARCIA  |
| Signature Of Applicant Phone Number  | Applicant, Please Print Name   |
| igarcia@homedynamics.com   |  |
| Applicant's e-mail address   | Contractor License # (Required unless built by owner)  |
| permit does not vest any rights to the property owner for follow all County procedures for permitting.   |  |
| Driveway must be constructed in accordance with the attached sketch. Applicant holds Lake County harmless work. Any deviation from the attached sketch must firs Please see attached minimum requirement details for spe Check one:  Clay Road — No apron required — culvert pipe many payed Road — Option 1: 6" limerock base and   | may be required — sod all disturbed areas.  Id minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 6" wire mesh placed a minimum of 10" from edge of oxidation   |
| Driveway must be constructed in accordance with the attached sketch. Applicant holds Lake County harmless work. Any deviation from the attached sketch must firs Please see attached minimum requirement details for spe Check one:  Clay Road — No apron required — culvert pipe may be required. Sod all pavement. Culvert pipe may be required.—Sod all   | s from all damages, claims, or injuries which may result from such stibe approved in writing by Lake County Public Works Department, acifications.  may be required — sod all disturbed areas.  and minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 6" wire mesh placed a minimum of 10' from edge of existing disturbed areas.  |
| Driveway must be constructed in accordance with the attached sketch. Applicant holds Lake County harmless work. Any deviation from the attached sketch must first Please see attached minimum requirement details for specific Check one:  Clay Road — No apron required — culvert pipe in Check one:  Clay Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x opavement. Culvert pipe may be required — Sod all In areas where sidewalks are present or planned, the driveway apron (at a maximum 1.5% cross slope) in comparison of the comparison o | s from all damages, claims, or injuries which may result from such stibe approved in writing by Lake County Public Works Department, acifications.  may be required — sod all disturbed areas.  and minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 6" wire mesh placed a minimum of 10' from edge of existing disturbed areas.  |
| Driveway must be constructed in accordance with the attached sketch. Applicant holds Lake County harmless work. Any deviation from the attached sketch must firs Please see attached minimum requirement details for spe Check one:  Clay Road — No apron required — culvert pipe in Clay Road — Option 1: 6" limerock base an concrete (3000 PSI) using 10 foot square of 6" x opavement. Culvert pipe may be required — Sod all In areas where sidewalks are present or planned, the driveway apron (at a maximum 1.5% cross slope) in common County Road #  | s from all damages, cialms, or injuries which may result from such stibe approved in writing by Lake County Public Works Department. ecifications.  may be required — sod all disturbed areas.  and minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 6" wire mesh placed a minimum of 10' from edge of existing disturbed areas.  driveway must include a minimum 4 foot wide path traversing the apliance with ADA requirements.   |
| Driveway must be constructed in accordance with the attached sketch. Applicant holds Lake County harmless work. Any deviation from the attached sketch must firs Please see attached minimum requirement details for spe Check one:  Clay Road — No apron required — culvert pipe in Clay Road — Option 1: 6" limerock base an concrete (3000 PSI) using 10 foot square of 6" x opavement. Culvert pipe may be required — Sod all In areas where sidewalks are present or planned, the driveway apron (at a maximum 1.5% cross slope) in common County Road #  | s from all damages, cialms, or injuries which may result from such sit be approved in writing by Lake County Public Works Department. sciffications.  may be required — sod all disturbed areas. Ind minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 6" wire mesh placed a minimum of 10' from edge of existing disturbed areas.  driveway must include a minimum 4 foot wide path traversing the apliance with ADA requirements.  Inpleted by County Staff  542046 Date: 7/19/18 Fee Code: PUBSV1   |
| Driveway must be constructed in accordance with the attached sketch. Applicant holds Lake County harmless work. Any deviation from the attached sketch must firs Please see attached minimum requirement details for spe Check one:  Clay Road — No apron required — culvert pipe in Clay Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x opavement. Culvert pipe may be required — Sod all In areas where sidewalks are present or planned, the driveway apron (at a maximum 1.5% cross slope) in composition of the comp | s from all damages, cialms, or injuries which may result from such sit be approved in writing by Lake County Public Works Department. sciffications.  may be required — sod all disturbed areas.  and minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 6" wire mesh placed a minimum of 10' from edge of existing disturbed areas.  driveway must include a minimum 4 foot wide path traversing the upliance with ADA requirements.  appleted by County Staff  542046 Date: 7/19/18 Fee Code: PUBSV1  Bigned:   |
| Driveway must be constructed in accordance with the attached sketch. Applicant holds Lake County harmless work. Any deviation from the attached sketch must firs Please see attached minimum requirement details for specheck one:  Clay Road — No apron required — culvert pipe in Check one:  Clay Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x of pavement. Culvert pipe may be required — Sod all In areas where sidewalks are present or planned, the driveway apron (at a maximum 1.5% cross slope) in common County Road # 7359  To be common Driveway Permit Fee: \$50.00 Check/Transaction #:  Permit # 160 27 Maint Area: 2 S  Permit Shall Expire One (1) Year From Date Approver   | s from all damages, claims, or injuries which may result from such stible approved in writing by Lake County Public Works Department. edifications.  may be required — sod all disturbed areas.  and minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 6" wire mesh placed a minimum of 10' from edge of existing disturbed areas.  driveway must include a minimum 4 foot wide path traversing the apliance with ADA requirements.  Inpleted by County Staff  572046 Date: 7/19/18 Fee Code: PUBSV1  Bigned: Date Expired:  |
| Driveway must be constructed in accordance with the attached sketch. Applicant holds Lake County harmless work. Any deviation from the attached sketch must first please see attached minimum requirement details for specheck one:  Clay Road — No apron required — culvert pipe in Check one:  Clay Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x opavement. Culvert pipe may be required — Sod all In areas where sidewalks are present or planned, the driveway apron (at a maximum 1.5% cross slope) in common County Road # 7359  To be common Driveway Permit Fee: \$50.00 Check/Transaction #:  Permit # 160 27 Maint Area: 2 S  Permit Shall Expire One (1) Year From Date Approver  | s from all damages, claims, or injuries which may result from such stible approved in writing by Lake County Public Works Department. edifications.  may be required — sod all disturbed areas.  and minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 6" wire mesh placed a minimum of 10' from edge of existing disturbed areas.  driveway must include a minimum 4 foot wide path traversing the apliance with ADA requirements.  Inpleted by County Staff  572046 Date: 7/19/18 Fee Code: PUBSV1  Bigned: Date Expired:  |
| Driveway must be constructed in accordance with the attached sketch. Applicant holds Lake County harmless work. Any deviation from the attached sketch must first please see attached minimum requirement details for specific Check one:  Clay Road — No apron required — culvert pipe in Check one:  Clay Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x of pavement. Culvert pipe may be required — Sod all In areas where sidewalks are present or planned, the driveway apron (at a maximum 1.5% cross slope) in composition of the com | s from all damages, claims, or injuries which may result from such stible approved in writing by Lake County Public Works Department. edifications.  may be required — sod all disturbed areas.  and minimum 1" Type S-III Asphalt. Option 2: 6"reinforced 6" wire mesh placed a minimum of 10' from edge of existing disturbed areas.  driveway must include a minimum 4 foot wide path traversing the apliance with ADA requirements.  Inpleted by County Staff  572046 Date: 7/19/18 Fee Code: PUBSV1  Bigned: Date Expired:  |

Public Works Department Road Operations Division

Public Works Department at 352-483-9000.

Entered Data One rst Scan dated Data Or

application. The driveway shall be constructed per approved subdivision plans if applicable. For inspection, call Lake County Building Services Division at 352-343-9634. For joint (Common Split) driveway inspection, call Lake County

> Residential Driveway Apron Permit Effective February 2015

nd Scan

Submit permit to Lake County Public Works, 437 Ardice Avenue, Eustis, FL 32726

d to (



## Residential Driveway Apron Permit Application Requirements

201804076

|                 | CANALON CONTRACTOR RECEIPED  |    |
|-----------------|--|----|
| <b>10.</b> 20.0 | To be completed by County Staff  |    |
|                 | Single Family Driveway (standard A) Joint Driveway (Common/Split) (standard B)  Permit Number  |    |
|                 | Driveway apron as Swale Check (standard C)<br>Piped Driveway apron (standard D)<br>Driveway apron conforming to Grade or Swale (standard E)  |    |
|                 | Driveway apron with Miami Curb & Guiter (standard M)<br>Driveway apron with Standard Curb & Guiter (standard S)  |    |
| *Th             | applicable driveway apron standard will be included with approved permit that is sent to applicant. *  |    |
| 1               | Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 Inches minimum thickness. (See detail on attachment).  | 쒜  |
| 2.              | To conform to skiewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 437 Ardice Avenue in Eustis.  |    |
| 3.              | Driveways are not permitted in the radius return of an intersection. Driveway aprons must be 100 feet from the nearest intersecting road and may not exceed 24 feet in width at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.   |    |
| Ą.              | Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.   |    |
|                 | If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of mitter to the end of mitter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be socided, matching existing grass type. Applicant shall be responsible for sod until it is established. |    |
| 6.              | Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.  |    |
| 7.              | Driveway permit shall expire one (1) year from date approved.  |    |
| 8.              | Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).  | /  |
| Iħ              | ave read and understand the above requirements   | 7/ |
|                 | Atta 18 orange of the Contract of the Same   | -  |

Public Works Department Road Operations Division

Residential Driveway Apron Permit Effective February 2015

LOT 353 GREATER LAKES PHASE ACCORDING TO THE PLAT THEREOF RECORDED IN PLAT BOOK 68, PAGES 82, 83 & 84 OF THE PUBLIC RECORDS OF LAKE COUNTY, FLORIDA. I understand that I have to meet all lot grading requirements as established in SUPERIOR BOULEVARD negrer 9 of the Level Development Regulations, I also certify that my development shall not proversely affect surrounding or down ream wetlands, fleadplains prinsiphyoning properties. Win 29 BO' PUBLIC RIGHT OF WAY GREATER LAKES PHASE 1 PLAT BOOK 61, PAGES 18-21 (1)  $\bigcirc$   $\triangle = 1.01,22$ 5' W.E. & L.E. Owngel Applicant Signature 2 R=2960.00'PLACID SO PUBLIC RIC 353 L=52.84'00.29 218 ② ∆=90'58'34" 111 N02"29"50"\ R=25.00'54"E L=39.70'がが ö 354 E ③ Δ=89°00'05" B ₹R NW S. R = 25.00'5.50 O L=38.83'00  $\bigoplus \Delta = 1.00'01"$ 19/57 R Minte Lunderstand that I shalf pleet all Single-Family Requirements as established in LDR 3.01-92 A) Residential Uses Classification of Uses. 18 R = 2844.00'ODY L = 49.65'% 10' U.E. My SO Owner/Applicant Signature The issuance of a zoning clarance does not assure that the setback sevel type TIMS

or that the development does not encroach on an easement. The graph of RIGHT OF WAY

contractor have the sole responsibility of compliance with serbacks and no
encroachment of easemblat and are responsible for bringing the property
into compliance. I hereby certify that the costs associated with meeting the
setbacks or restoring exemplis are-my responsibility. No grass (except Bahlagrass)
can cover more than 60% of the previous landscape area and all grass must be
irrigated separately.

DRAINAGE TYPE: "A"

NOWLATES SOME REMAR & CAP (BYC) OR

NOWLESS NOTED OTHERWISE

- MIDICATES CERTIFICATION CONTROL POINT

IRRIGATION OF THE CONTROL POINT

TO BUILDING SETBACK UP. — HOLD PIPE NOTICE TO OWNER AND CONTRACTOR BUILDING SETBACKS: 7-22-2016 FRONT=20' REAR=20' SIDE=5.5 CORNER=15' 50' FROM WETLAND LINES irrigated separately.

SECOND SURVEY REPORT/NOTES: LEGEND [S] - MOICATES (
5/8 = SULDING SETBACK
MAINT MAINTENANCE
UTIL UTILITY
CONCEPTE
ON CONCEPTE
ON WHEN REFER
CONCEPTE
ON WHEN REFER
CONCEPTE
ON WHEN REFER
CONCEPTE
ON WHEN REFER
THOSE FLOOR
WHEN REFER
THOSE FLOOR
TRANSFORMER
ALVE
ESMT. = EASEMENT
TRANSFORMER
ALVE
ESMT. = EASEMENT
TRANSFORMER
TRANSFORMER
TRANSFORMER
TRANSFORMER
TRANSFORMER
TRANSFORMER
TRANSFORMER
TRANSFORMER
TOP. = PLAT BOOK
P. = PLAT PLAN
H. = PLAT PLAN
H. = CALCULTY RISER
P.O.L. = POINT ON LINE SURVEY MAP AND REPORT OR THE COPIES THEREOF ARE NOT VALID WITHOUT THE SIGNATURE AND THE ORIGINATING MAPPER. LIP. = HON PIPE

S/W = SDEWALK

S/W = SDEWALK

LR = HON ROB

LR = HON RO BUILDING APPARENT PHYSICAL USE, INCLUDING BUT NOT UNITED TO, DRIVEWAYS, SIDEWALKS AND UTILITIES ARE AS SIGNAL OWNER'S GIGNALUSE OF THEREON.

OWNER'S GIGNALUSE THEREON ARE IN FEET AND DECIMALS Contractor's Signature Thereof,

Wikess noted otherwise, no underground improvements
foundations/foother or rode overhangs have been
Located. Entrachement accorditions and governmental
regurements not determined by surveyor. MON-RADIAL

ARC
LEHOTH
CHORD BEARING
SIDEWALK EASEMENT
LANDSCAPE EASEMENT
LANDSCAPE EASEMENT
UTILITY EASEMENT
UTILITY EASEMENT MODEL OPTIONS: GARAGE RIGHT 3 CAR GARAGE OWNERSHIP OF SUBJECT PROPERTY AND IMPROVEMENTS UNDETERMINED BY SURVEYOR. THIS MAP IS INTENDED TO BE DISPLAYED AT A SCALE LOT SHOWN HEREON CONTAINS 8,576 SQ. FT., MORE OR LESS BUILDING TIES ARE NOT TO BE USED TO CONSTRUCT DEED ON PLATTED LINES or payled unes the lands shown hereon were not abstracted for easements, rights of way, restrictions, uses, ownership or matters of record by this firm, == PERMANENT REFERENCE MONUMENT
== ELECTRICAL JUNCTION BOX
= NORTH AMERICAN VERTICAL DATUM
== NATIONAL GEODETIO VERTICAL DATUM
== PRIVATE ALLEY EASEMDT
== PERMANENT CONTROL PONT
== PERMANENT REFERENCE MONUMENT

\$\times\$ DELTA THE RELATIVE ACCURACY OF FIELD MEASURED CONTROL EXCEEDS 1 FOOT IN 10,000 FEET. CERTIFIED TO: BEARINGS ARE BASED UPON THE CENTERLINE OF PLACID PLACE PER RECORD PLAY, HAYING A BEARING OF N 02'29'50" W. FLORIDA COMMUNITY BANK, N.A. ITS SUCCESSORS AND/OR ASSIGNS HOME DYNAMICS SAWGRASS, LLC. BEARINGS AND DISTANCES SHOWN HEREON ARE MEASURED AND PER RECORDED PLAT/LEGAL DESCRIPTION UNLESS OTHERWISE NOTED. ELECTRONIC FILE: IF THIS FILE WAS SIGNED ELECTRONICALLY BY SURVEYOR AS NOTED IN SIGNATURE BLOCK, ON THE DATE AND/OR THE STAMP SHOWN USING A DIGITAL SIGNATURE, PRINTER COPIES OF THIS ARE NOT CONSIDERED SIGNED AND SEALED AND THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPY, OLD REPUBLIC NATIONAL TITLE INSURANCE COMPANY THE PROPERTY SHOWN HEREON APPEARS TO LIE IN ZONE X PER F.A.R.M. MAP PANEL NO. 1206900675E, DATED DECEMBER 18, 2012. THE FLOOD INSURANCE RATE MAP IS NOT A SURVEY, FLOOD ZONE DETERMINATION IS AN OPINION ONLY. AKERMAN, LLP. LIMITATION OF LIABILITY: RELIANCE ON THIS SURVEY IS RESTRICTED TO THOSE PARTIES LISTED AS "CERTIFIED TO" ON THE FACE OF THIS SURVEY. POTENTIAL BOUNDARY INCONSISTENCIES OBSERVEDI (NOT A SURVEY)
PROPOSED HOUSE LOCATION
DATE MODEL
6-12-2018 B-ELEV "B" (PH1) NOTICE OF COPYRIGHT: ADDITIONS OR DELETIONS TO SURVEY MAPS OR REPORTS BY OTHER THAN SIGNING PARTY OR PARTES IS PONUBITED WITHOUT WRITTEN CONSENT OF THE SIGNING PARTY OR PARTIES. ELEVATIONS, IF SHOWN, ARE BASED ON BENCHMARK PROVIDED BY CLIENT (NAVD 88). I CERTIFY THAT THIS MEETS OR EXCEEDS THE STANDARDS OF PRACTICE SET FORTH BY THE FLORIDA BOARD OF PROFESSIONAL SURVEYORS AND MAPPERS IN CAPPER S. 17, FLORIDA JOURNISTITATIVE CODE, PURSUANT TO SECTION 472.027, FLORIDA STATUTES. PREPARED FOR BOUNDARY SURVEY Home Dynamics FORMBOARD LOCATION PREPARED BY Associated Land Surveying & Mapping, Inc. FOUNDATION CERTIFIED FORE ASSOCIATED LAND SURVEYING 1681 POWELL STREET
LONGWOOD, FLORIDA 32750
PHONE: (407) 869-5002 FAX: (407) 869-8393 FINAL BOUNDARY SURVEY

Certificate of Authorization Number: LB 6767

SCALE

1" == 40'

EMAIL: alsm@alsm.net

JOB NO.

09096

DAVID M. Modermott, Certificate No. 4779

DJACK D. REED JR., CERTIFICATE No. 5737
FLORIDA REGISTERED SURVEYOR AND MAPPER