LAKE COUNTY Per	tial Driveway Apron mit Application ease Print or Type) 18000450   3[553]   30   5   28  Alt. Key# Section Township Range 56177 6th St.  House Number / Road Name	
Applicant's City, State, Zip	Subdivision Name	
Applicant's e-mail address  A driveway permit is required to construct a new driving anterpressible to the construct and	Contractor License # (Required unless built by owne	
follow all County procedures for permitting.  Driveway must be constructed in accordance with the Lake County Land Development Regulations and as shown on the attached sketch. Applicant holds Lake County harmless from all damages, claims, or injuries which may result from such work. Any deviation from the attached sketch must first be approved in writing by Lake County Public Works Department. Please see attached minimum requirement details for specifications.  Clay Road — No apron required — culvert pips may be required — sod all disturbed areas.  Paved Road — Option 1: 6" limerock base and minimum 1" Type S-XII Asphalt. Option 2: 6"reinforced concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10" from edge of existing pavement. Culvert pips may be required — Sod all disturbed areas.  In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.		
Driveway Permit Fee: \$50.00 Check/Transaction #:  Permit # 16046 Maint Area: 3 Si  Permit Shall Expire One (1) Year From Date Approve  Date of Final Inspection: I	sctor:  The non-maintained portion  Required  Should meet the regulations, and requirements as noted on this proved subdivision plans if applicable. For inspection, call Lake for Joint (Common Split) driveway inspection, call Lake	
Road Operations Division	Residential Driveway Apron Permit  8 / 1/68  Effective June 2015	

Entered Data One Solids

ret Scan Solids

dated Data One Solids

rond Scor Solids

med 3/24/8



## Residential Driveway Apron Permit Application Requirements

Ploking Permit Application Requirements		
To be completed by County Staff	<del></del>	
Single Family Driveway (standard A)  Joint Driveway (Common/Split) (standard B)  Permit Number		
Driveway apron as Swale Check (standard C) Plped Driveway apron (standard D) Driveway apron conforming to Grade or Swale (standard E)  Driveway apron with Miami Curb & Gutter (standard M) Driveway apron with Standard Curb & Gutter (standard S)		
Driveway apron with Miami Curb & Gutter (standard M) Driveway apron with Standard Curb & Gutter (standard S)		
*The applicable driveway apron standard will be included with approved permit that is sent to applican	<u>t. *</u>	
<ol> <li>Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inch minimum thickness. (See detail on attachment).</li> </ol>	ės	
<ol> <li>To conform to sidewalk requirements, subdivision construction plans are available for review in Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.</li> </ol>		
<ol> <li>Driveways are not permitted in the radius return of an intersection. Driveway aprons must be feet from the nearest intersecting road and may not exceed 24 feet in width at the edge of roadway. Variance requests should be submitted to the Lake County Public Works Department.</li> </ol>	' tha	
4. Pavers Installed as a driveway apron are the resident's responsibility to maintain, replace an repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utinstallation and/or maintenance, the paver(s) used as replacements may not be able to be match.	tility ied.	
5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inche diameter and a minimum of 30 feet in length measured from the end of miter to the end of	s in iter.	
6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the L County Public Works Department. In areas where sidewalks are present or planned, the driven must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cr slope) in compliance with ADA requirements.	eke Vay Toss	
7. Driveway permit shall expire one (1) year from date approved.		
B. Drīveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).	of	
I have read and understand the above requirements		
Applicant's Signature/Date		
Public Works Department		

Public Works Department Road Operations Division

Residential Driveway Apron Permit Effective June 2015

