

Date: \_\_\_

## **Residential Driveway Apron** Permit Application (Please Print or Type)

Bldg Permit No. \_\_\_

JUN 2 5 2018

LAKE COLDEN 2018061074

Date: bldg Permit No.	
HOME DYNAMICS	3906109, 10 1 24 1 26
Name Permit Will Be Returned To:	Alt. Key# Section Township Range
1755 TECHNOLOGY WAY #210	18016 Placid Place
Street Address	House Number / Road Name
BOCA RATON, FL 33431	GREATER LAKES LOT
City, State, Zip (954)	Subdivision Name
914-0246	ISMAEL GARCIA
Signature Of Applicant Phone Number	Applicant, Please Print Name
igarcia@homedynamics.com	
Applicant's e-mail address	Contractor License # (Required unless built by owner)
attached sketch. Applicant holds Lake County harmless	ake County Land Development Regulations and as shown on the from all damages, claims, or injuries which may result from such be approved in writing by Lake County Public Works Department.
Check one:  Clay Road — No apron required — culvert pipe may Paved Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6 pavement. Culvert pipe may be required — Sod all during areas where sidewalks are present or planned, the direction of the square of the direction of the square of the	ay be required – sod all disturbed areas.  I minimum 1" Type S-III Asphalt. Option 2: 6"reinforced" wire mesh placed a minimum of 10' from edge of existing listurbed areas.  riveway must include a minimum 4 foot wide path traversing the
Check one: Clay Road – No apron required – culvert pipe may Paved Road – Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required – Sod all did In areas where sidewalks are present or planned, the did driveway apron (at a maximum 1.5% cross slope) in complete County Road # 0357A  To be complete the complete required – Sod all did not be completed.	ay be required – sod all disturbed areas. I minimum 1" Type S-III Asphalt. Option 2: 6"reinforced" wire mesh placed a minimum of 10' from edge of existing listurbed areas.  riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  pleted by County Staff
Check one: Clay Road – No apron required – culvert pipe may be required – County Road – Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required – Sod all do In areas where sidewalks are present or planned, the didriveway apron (at a maximum 1.5% cross slope) in complete County Road # 0357A To be county Road # 0357A To be county Road	ay be required – sod all disturbed areas. If minimum 1" Type S-III Asphalt. Option 2: 6"reinforced" wire mesh placed a minimum of 10' from edge of existing disturbed areas.  Triveway must include a minimum 4 foot wide path traversing the diance with ADA requirements.  Deleted by County Staff  544220 Date: 8/14/18 Fee Code: PUBSV1
Check one: Clay Road — No apron required — culvert pipe may have Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6 pavement. Culvert pipe may be required — Sod all d In areas where sidewalks are present or planned, the didriveway apron (at a maximum 1.5% cross slope) in complete County Road # 0357A To be complete To be comple	ay be required – sod all disturbed areas. I minimum 1" Type S-III Asphalt. Option 2: 6"reinforced" wire mesh placed a minimum of 10' from edge of existing listurbed areas.  riveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  pleted by County Staff
Check one: Clay Road — No apron required — culvert pipe may be required — County Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6 pavement. Culvert pipe may be required — Sod all done of the dividence of the dividence of the dividence of the complex o	ay be required – sod all disturbed areas. If minimum 1" Type S-III Asphalt. Option 2: 6"reinforced " wire mesh placed a minimum of 10' from edge of existing disturbed areas.  Triveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Detected by County Staff  S44220 Date: 8/14/18 Fee Code: PUBSV1  Bate Approved:
Check one: Clay Road — No apron required — culvert pipe may have Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required — Sod all done of the dividence o	ay be required – sod all disturbed areas. If minimum 1" Type S-III Asphalt. Option 2: 6"reinforced" wire mesh placed a minimum of 10' from edge of existing listurbed areas.  Triveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  The pleted by County Staff  S44220 Date: 8/14/18 Fee Code: PUBSV1  gned: Date Approved:
Check one: Clay Road — No apron required — culvert pipe may be required — Clay Road — Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required — Sod all d In areas where sidewalks are present or planned, the driveway apron (at a maximum 1.5% cross slope) in composition of the composition o	ay be required – sod all disturbed areas. If minimum 1" Type S-III Asphalt. Option 2: 6"reinforced" wire mesh placed a minimum of 10' from edge of existing listurbed areas.  Triveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  The pleted by County Staff  S44220 Date: 8/14/18 Fee Code: PUBSV1  gned: Date Approved:
Check one: Clay Road – No apron required – culvert pipe may Paved Road – Option 1: 6" limerock base and concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required – Sod all duriveway apron (at a maximum 1.5% cross slope) in composition of the comp	ay be required — sod all disturbed areas. If minimum 1" Type S-III Asphalt. Option 2: 6"reinforced "wire mesh placed a minimum of 10' from edge of existing listurbed areas.  Triveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  The pleted by County Staff  S44220 Date: 8/14/18 Fee Code: PUBSV1  gned: Date Approved:
Check one: Clay Road — No apron required — culvert pipe may be required — culvert pipe may be required — Sod all do not square of 6" x 6" pavement. Culvert pipe may be required — Sod all do not requir	ay be required — sod all disturbed areas. If minimum 1" Type S-III Asphalt. Option 2: 6"reinforced " wire mesh placed a minimum of 10' from edge of existing listurbed areas.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Investigation of the lian
Check one: Clay Road — No apron required — culvert pipe may be readed — Concrete (3000 PSI) using 10 foot square of 6" x 6" pavement. Culvert pipe may be required — Sod all double of the diveway apron (at a maximum 1.5% cross slope) in completion application. The design has been reviewed and upon completion application. The driveway shall be constructed per ap County Building Services Division at 352-343-9634. Fublic Works Department at 352-483-9000.	ay be required — sod all disturbed areas. If minimum 1" Type S-III Asphalt. Option 2: 6"reinforced " wire mesh placed a minimum of 10' from edge of existing listurbed areas.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Inveway must include a minimum 4 foot wide path traversing the liance with ADA requirements.  Investigation of the lian



## Residential Driveway Apron Permit Application Requirements

To be completed by County Staff
XXSingle Family Driveway (standard A)  ☐ Joint Driveway (Common/Split) (standard B)  ☐ Permit Number
☐ Driveway apron as Swale Check (standard C) ☐ Piped Driveway apron (standard D) ☐ Driveway apron conforming to Grade or Swale (standard E)
☐ Driveway apron with Miami Curb & Gutter (standard M) ☐ Driveway apron with Standard Curb & Gutter (standard S)
*The applicable driveway apron standard will be included with approved permit that is sent to applicant. *
<ol> <li>Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment).</li> </ol>
<ol><li>To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 437 Ardice Avenue in Eustis.</li></ol>
<ol> <li>Driveways are not permitted in the radius return of an intersection. Driveway aprons must be 100 feet from the nearest intersecting road and may not exceed 24 feet in width at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.</li> </ol>
4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
7. Driveway permit shall expire one (1) year from date approved.
8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).
I have read and understand the above requirements through the

Public Works Department Road Operations Division

Residential Driveway Apron Permit Effective February 2015

Applicant's Signature/Date