

## Residential Driveway Apron

JULU 1 2018

AKE COUNTY Permi	t Application	20	000	6 J GAIN
- 7/10/18	e Print or Type)		PUBLICY	03997
Weekley Homes, LLC				the continues of the second se
Name Permit Will Be Returned To:	3910332	<sub>/</sub> 26	<sub>/</sub> 22	<sub>/</sub> 26
225 S. Westmonte Dr. #2000	Alt. Key#	Section	Township	Range
Street Address	13343 Sh	ady Hol	low Loop	
Altamonte Spgs., FL 32714	House Number			
City, State, Zip	Johns Lak	e Landi	ing	1
	Subdivision Nar			
Signature Of Applicants  407-865-8294  Phone Number	Alexis Cod	•		
) in the state of	Applicant, Pleas		ne	
Acostor Odwhowes. Com Applicant's e-mail address	CBC1254			
	Contractor Lice	nse # (Red	quired unless	built by owner)
A driveway permit is required to construct a new driveward install a temporary construction entrance within the public permit does not vest any rights to the property owner for follow all County procedures for permitting.	ay, modify an existing (	driveway to	meet county i	requirements on
Driveway must be constructed in accordance with the Lake County Land Development Regulations and as shown on the attached sketch. Applicant holds Lake County harmless from all damages, claims, or injuries which may result from such work. Any deviation from the attached sketch must first be approved in writing by Lake County Public Works Department. Please see attached minimum requirement details for specifications.  Check one:  Clay Road — No apron required — culvert pipe may be required — sod all disturbed areas.  Paved Road — Option 1: 6" limerock base and minimum 1" Type S-III Asphalt. Option 2: 6"reinforced concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of existing pavement. Culvert pipe may be required — Sod all disturbed areas.  In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.				
Courts D. 111 Indian	eted by County Staff			
20 NO COMPA				
The second secon	544578 Date:	8/11/18	Fee Co	de: PUBSV1
Permit # 16045 Maint Area: 2 Sign	ed:		Date Approved	1.
Permit Shall Expire One (1) Year From Date Approved				1:
Date of Final Inspection:	Date Expired:			
Date of Final Inspection: Inspecto	OF;			
Comments or special conditions:				
The design has been reviewed and upon completion should meet the regulations and requirements as noted on this application. The driveway shall be constructed per approved subdivision plans if applicable. For inspection, call Lake County Building Services Division at 352-343-9634. For joint (Common Split) driveway inspection, call Lake County Public Works Department at 352-483-9000.  Submit permit to Lake County Public Works, 437 Ardice Avenue, Eustis, FL 32726				
Public Works Donorton of	, , , , , , ,			

Public Works Department Road Operations Division

Residential Driveway Apron Permit Effective February 2015

Data One .to One ilu Scan med to Client



## Residential Driveway Apron

	Permit Application Requirements
	To be completed by County Staff
	Single Family Driveway (standard A)  Joint Driveway (Common/Split) (standard B)  Permit Number
	Driveway apron as Swale Check (standard C) Piped Driveway apron (standard D) Driveway apron conforming to Grade or Swale (standard E)
	Driveway apron with Miami Curb & Gutter (standard M) Driveway apron with Standard Curb & Gutter (standard S)
*The	e applicable driveway apron standard will be included with approved permit that is sent to applicant, *
1.	Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment).
2.	To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 437 Ardice Avenue in Eustis.
3.	Driveways are not permitted in the radius return of

- Driveways are not permitted in the radius return of an intersection. Driveway aprons must be 100 feet from the nearest intersecting road and may not exceed 24 feet in width at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
- Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or 4. repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
- If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If 5. there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
- Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake 6. County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
- Driveway permit shall expire one (1) year from date approved. 7.

Driveway Apron Permit Application shall include a check made payable to the Lake County Board of 8. County Commissioners (BOCC).

I have read and understand the above requirements\_

Applicant's Signature Date

Public Works Department Road Operations Division

Residential Driveway Apron Permit Effective February 2015