




Residential Driveway Apron Permit Application

(Please Print or Type)



Date: 09/12/18

Bldg Permit No. _____

Mario Garcia

1222591 / 11 / 18 / 27

Applicant/ Name Permit Will Be Returned To:

Alt. Key# Section Township Range

4914 Havilland Dr.

(land) county road 439 Umatilla 32787

Applicant's Street Address

House Number / Road Name

Mount Dora, Fl. 32757

none

Applicant's City, State, Zip

Subdivision Name

Mario Garcia Digitally signed by Mario Garcia
DN: cn=Mario Garcia, o. os,
email=mario_garcia42@hotmail.com, c=US
Date: 2018.09.12 10:21:38 -0400 352-223-4125

Mario Garcia

Signature of Applicant

Phone Number

Applicant, Please Print Name

mario_garcia42@hotmail.com

Owner

Applicant's e-mail address

Contractor License # (Required unless built by owner)

A driveway permit is required to construct a new driveway, modify an existing driveway to meet county requirements, or install a temporary construction entrance within the public rights-of-way of County maintained roads. Issuance of a driveway permit does not vest any rights to the property owner for zoning, land use changes, or site improvements. The owner must follow all County procedures for permitting.

Driveway must be constructed in accordance with the Lake County Land Development Regulations and as shown on the attached sketch. Applicant holds Lake County harmless from all damages, claims, or injuries which may result from such work. Any deviation from the attached sketch must first be approved in writing by Lake County Public Works Department. Please see attached minimum requirement details for specifications.

Check one:

- Clay Road – No apron required – culvert pipe may be required – sod all disturbed areas.
- Paved Road – Option 1: 6" limerock base and minimum 1" Type S-III Asphalt. Option 2: 6" reinforced concrete (3000 PSI) using 10 foot square of 6" x 6" wire mesh placed a minimum of 10' from edge of existing pavement. Culvert pipe may be required – Sod all disturbed areas.

In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.

County Road # <u>7483</u>	To be completed by County Staff		
Driveway Permit Fee: \$50.00	Check/Transaction #: <u>Credit Card</u>	Date: <u>9/12/18</u>	Fee Code: PUBSV1
Permit # <u>16116</u>	Maint Area: <u>3</u>	Signed: _____	Date Approved: _____
Permit Shall Expire One (1) Year From Date Approved		Date Expired: _____	
Date of Final Inspection: _____	Inspector: _____		
Comments or special conditions: _____			
<p>The design has been reviewed and upon completion should meet the regulations and requirements as noted on this application. The driveway shall be constructed per approved subdivision plans if applicable. For inspection of a driveway associated with a building permit, call Lake County Building Services Division at 352-343-9634. For inspection of a joint (Common Split) driveway or a driveway not associated with a building permit, call Lake County Public Works Department at 352-253-6019. Submit permit to: Lake County Public Works, Post Office Box 7800, Tavares, FL 32778</p>			

Public Works Department
Road Operations Division

Entered Data One 9/18/18
 2nd Scan 9/18/18
 3rd Scan _____
 4th Scan _____
 5th Scan _____
 6th Scan _____
 7th Scan _____
 8th Scan _____
 9th Scan _____
 10th Scan _____
 11th Scan _____
 12th Scan _____
 13th Scan _____
 14th Scan _____
 15th Scan _____
 16th Scan _____
 17th Scan _____
 18th Scan _____
 19th Scan _____
 20th Scan _____
 21st Scan _____
 22nd Scan _____
 23rd Scan _____
 24th Scan _____
 25th Scan _____
 26th Scan _____
 27th Scan _____
 28th Scan _____
 29th Scan _____
 30th Scan _____

Residential Driveway Apron Permit
Effective February 2017



Residential Driveway Apron Permit Application Requirements

To be completed by County Staff

- Single Family Driveway (standard A)
- Joint Driveway (Common/Split) (standard B)
- Driveway apron as Swale Check (standard C)
- Piped Driveway apron (standard D)
- Driveway apron conforming to Grade or Swale (standard E)
- Driveway apron with Miami Curb & Gutter (standard M)
- Driveway apron with Standard Curb & Gutter (standard S)

Permit Number

*The applicable driveway apron standard will be included with approved permit that is sent to applicant. *

1. Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment).
2. To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
3. Driveways are not permitted in the radius return of an intersection. With the exception of joint driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10 feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4 foot wide flares on either side of the driveway, for a maximum width of 32' at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
7. Driveway permit shall expire one (1) year from date approved.
8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements

Mario Garcia

Digitally signed by Mario Garcia
DN: cn=Mario Garcia, o, ou,
email=mario_garcia42@hotmail.com, c=US
Date: 2018.09.12 10:24:18 -04'00'

Applicant's Signature/Date

Public Works Department
Road Operations Division

Residential Driveway Apron Permit
Effective February 2017

RECEIPT

LAKE COUNTY BOCC
315 W MAIN ST
Tavares , FL 32778
Phone

Transaction Type : Sale

Comment :

Merchant-Defined Data Fields

Merchant-Defined Data Field 1 : Residential Driveway Apron Permit
Department : Public Works
Merchant-Defined Data Field 3 : 5056260.341213

Total : 50.50 USD

Cardholder Information

Name Mario Garcia, Jr.
Credit Card Type : Visa
Credit Card Number : #####6672

Company :
Phone : 3522234125
Email : mario_garcia42@hotmail.com