

## Residential Driveway Apron Permit Application

	FLORIDA	(Please	a Print or Type)	I AKE MAI
<b>'.</b>	Date:	Bldg Permit No. 2018	3060935	SEP 0 4 2018
	Applicant/ Name Permit		3789629/ Alt. Key# Sec	36 / 22 / 26 ction Township Range
	15031 C.	edar Branch Wa.	Champ	agne Drive
	Applicant a Street Addre	SS	House Number / Ro	ad Name
	Applicant's City, State, 2	FC 32824	Subdivision Name	
	Signature of Applicant	Phone Number	Applicant, Please Pr	D Rahmah Int Name
12 fg 22 11	Derm. Hing Salur Applicant's e-mall addre	trons, com	CBCO	≤309 → # (Required unless built by owner)
		ights to the property owner for	ay, modify an existing drive	way to meet county requirements, or ntained roads. Issuance of a driveway site improvements. The owner must
	work. Any deviation from		rom all damages, claims, or he approved in writing by La	nt Regulations and as shown on the injuries which may result from such ake County Public Works Department.
	☐ Clay Road - No apro ☐ Paved Road - Option concrete (3000 PSI) usi	on required — culvert pipe ma on 1: 6" limerock base and ng 10 foot square of 6" x 6" may be required — Sod all dis	minimum 1" Type S-III /	sturbed areas. Asphalt. Option 2: 6"reinforced num of 10" from edge of existing
_	In areas where sidewalks :		veway must include a minin	num 4 foot wide path traversing the
	County Road # /067	'A To be compl	eted by County Staff	
	Driveway Permit Fee: \$5	0.00 Check/Transaction#: 5		1//8 Fee Code: PUBSV1
	Permit # 16120	Maint Area: 2 Sign	*	The state of the s
	-	3		
		() Year From Date Approved Inspect		
				. 11
	Conduction of special counti	ons:		
	County Building Services 1 Public Works Department	snan de constructed per appr Division at 352-343-9634. For at 352-253-6019	oved subdivision plans if a joint (Common Split) dri	and requirements as noted on this pplicable. For inspection, call Lake veway inspection, call Lake County
	Submit permit to: Lake Co	unty Public Works, Post Off	ice Box 7800, Tavares, F	L 32778
	Public Works Department Road Operations Division		Re	esidential Driveway Apron Permit
	TOWN OPPORTUDING DIVISION	Entered Data One _		Effective June 2015
	<b>'</b> ,	st Scan tared Data One	9/18/13	



## Residential Driveway Apron Permit Application Requirements

Ī		FEOREDA.			
		To be completed by County Staff			
		Single Family Driveway (standard A) Joint Driveway (Common/Split) (standard B) Permit Number			
		Driveway apron as Swale Check (standard C) Piped Driveway apron (standard D) Driveway apron conforming to Grade or Swale (standard E)			
		Driveway apron with Miami Curb & Gutter (standard M) Driveway apron with Standard Curb & Gutter (standard S)			
	*The	applicable driveway apron standard will be included with approved permit that is sent to applicant. *			
	1.	Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment).			
	2,	To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.			
	3,	Driveways are not permitted in the radius return of an intersection. Driveway aprons must be 100 feet from the nearest intersecting road and may not exceed 24 feet in width at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.			
	4,	Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.			
	5.	If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.			
	6 <b>.</b>	Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.			
	7.	Driveway permit shall expire one (1) year from date approved.			
	8,	Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).			
	I have read and understand the above requirements \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \				
	.,	Applicant's Signature/Date			

Public Works Department Road Operations Division Residential Driveway Apron Permit Effective June 2015

