

Residential Driveway Apron Permit Application

| Application | New Later Control | |
|----------------|-------------------|--|
| Print or Type) | | |
| T. | LAKE COLINTY. | |

| (Please P | rint or Type) |
|--|--|
| Date: 9-18-18 Bldg Permit No. | LAKE COUNTY |
| Brent Rigby | 1483336 ,6 ,18 ,24 |
| Applicant/ Name Permit Will Be Returned To: | Alt. Key# Section Township Range |
| 16362 SE 81st Terrace | 1318 Debra Drive |
| Applicant's Street Address | House Number / Road Name |
| Summerfield, FL 34491 | Orange Blossom Gardens , |
| Applicant's City, State, Zip | Subdivision Name |
| 19391 951-314-4556 | Brent Rigby |
| Signature of Applicant Phone Number | Applicant, Please Print Name |
| Brentdrigby@aol.com | CGC1517353 |
| Applicant's e-mail address | Contractor License # (Required unless built by owner) |
| install a temporary construction entrance within the public ri | y, modify an existing driveway to meet county requirements, or ghts-of-way of County maintained roads. Issuance of a driveway oning, land use changes, or site improvements. The owner must |
| attached sketch. Applicant holds Lake County harmless frowork. Any deviation from the attached sketch must first be Please see attached minimum requirement details for specific Check one: Clay Road — No apron required — culvert pipe may Paved Road — Option 1: 6" limerock base and reconcrete (3000 PSI) using 10 foot square of 6" x 6" very pavement. Culvert pipe may be required — Sod all distance. | y be required – sod all disturbed areas. minimum 1" Type S-III Asphalt. Option 2: 6"reinforced wire mesh placed a minimum of 10' from edge of existing turbed areas. Yeway must include a minimum 4 foot wide path traversing the |
| County Road # 790/E To be comple | eted by County Staff |
| Driveway Permit Fee: \$50.00 Check/Transaction #: | Date: Fee Code: PUBSV1 |
| Permit # 16148 Maint Area: 1 Sign | ed: Date Approved: |
| Permit Shall Expire One (1) Year From Date Approved | Date Expired: |
| Date of Final Inspection: Inspect | or: |
| Comments or special conditions: Applicat is reques | |
| Comments of special conditions. The property of the conditions of special conditions. | strang of freit existing aprox. |
| application. The driveway shall be constructed per a driveway associated with a building permit, call Lak inspection of a joint (Common Split) driveway or a driv | nould meet the regulations and requirements as noted on this pproved subdivision plans if applicable. For inspection of a ke County Building Services Division at 352-343-9634. For reway not associated with a building permit, call Lake County permit to: Lake County Public Works, Post Office Box 7800, |
| Public Works Department Road Operations Division | Residential Driveway Apron Permit |

d Data One



Residential Driveway Apron Permit Anniication Requirements

| The state of the s | | |
|--|---------------|--|
| To be completed by County Staff | <u> </u> | |
| ☐ Single Family Driveway (standard A) ☐ Joint Driveway (Common/Split) (standard B) | Permit Number | |
| Driveway apron as Swale Check (standard C) Piped Driveway apron (standard D) Driveway apron conforming to Grade or Swale (standard E) | :) | |
| ☐ Driveway apron with Miami Curb & Gutter (standard M) ☐ Driveway apron with Standard Curb & Gutter (standard S) | | |
| *The applicable driveway apron standard will be included with approved permit that is sent to applicant. * | | |
| 1. Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches | | |

- To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N, Sinclair Avenue in Tavares,
- Driveways are not permitted in the radius return of an intersection. With the exception of joint driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10 feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4 foot wide flares on either side of the driveway, for a maximum width of 32' at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
- Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
- If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
- Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
- 7. Driveway permit shall expire one (1) year from date approved.

Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements

Applicant's Signature/Date

Public Works Department Road Operations Division Residential Driveway Apron Permit Effective February 2017

