

Residential Driveway Apron Permit Application (Please Print or Type)

Bldg Permit 40 180 5 1 3 6 4

| Kenneth Smith | 3907906, 13, 24, 26 |
|---|--|
| Applicant/ Name Permit Will Be Returned To: | Alt. Key# Section Township Range |
| 4901 Vineland Road | 17329 Bracker Fern Lane |
| Applicant's Street Address | House Number / Road Name |
| Orlando, FL 32811 | SERENOA / 385 |
| Applicant's City, State, Zip | Subdivision Name |
| hunde 407-661-2161 | Kenneth Smith |
| Signature of Applicant Phone Number | Applicant, Please Print Name |
| NFLPermitting@Pulte.com | CGC 1520694 |
| Applicant's e-mail address | Contractor License # (Required unless built by owner) |
| A driveway permit is required to construct a new driveway, minstall a temporary construction entrance within the public rights permit does not vest any rights to the property owner for zonin follow all County procedures for permitting. | s-of-way of County maintained roads. Issuance of a driveway |
| Driveway must be constructed in accordance with the Lake C attached sketch. Applicant holds Lake County harmless from work. Any deviation from the attached sketch must first be applease see attached minimum requirement details for specification Check one: | all damages, claims, or injuries which may result from such oproved in writing by Lake County Public Works Department. |
| Clay Road — No apron required — culvert pipe may be Paved Road — Option 1: 6" limerock base and min concrete (3000 PSI) using 10 foot square of 6" x 6" wire pavement. Culvert pipe may be required — Sod all disturbances. | imum 1" Type S-III Asphalt. Option 2: 6"reinforced e mesh placed a minimum of 10' from edge of existing |
| In areas where sidewalks are present or planned, the drivewa | ay much include a minimum 4 foot wide path traversing the |

driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.

| Permit # | e: \$50.00 Check/Trans Maint Area: | | | Date Approved: | e: PUBSV1 |
|--|--|---|---|---|--|
| Permit Shall Expire | One (1) Year From Dat | te Approved | Date Expired: | : : | |
| Date of Final Inspection | on: | Inspector: | | <u> </u> | |
| Comments or special | conditions: | · | | <u></u> | · · · · |
| application. The driveway associated inspection of a joint | reviewed and upon c veway shall be constr with a building per (Common Split) drive rtment at 352-253-601 | ructed per approve mit, call Lake Cou way or a driveway | d subdivision plans unty Building Service not associated with a | if applicable. For inces Division at 352-3 building permit, call | nspection of a 343-9634. For Lake County |



Residential Driveway Apron Permit Application Requirements

| To be completed by County Staff | | | | | |
|---|---------------------------|---------------|--|--|--|
| ☐ Single Family Driveway (standard A)☐ Joint Driveway (Common/Split) (standard B) | Permit Number | - '' ::1'3 | | | |
| Driveway apron as Swale Check (standard C) Piped Driveway apron (standard D) Driveway apron conforming to Grade or Swale (standard E) | | | | | |
| Driveway apron with Miami Curb & Gutter (standard M) Driveway apron with Standard Curb & Gutter (standard S) | | | | | |
| *The applicable driveway apron standard will be included with approved pe | ermit that is sent to app | olicant. * | | | |

- 1. Sidewalks must be constructed per FDOT Index 310, with maximum cross slope of 1.5%, 6 inches minimum thickness. (See detail on attachment).
- 2. To conform to sidewalk requirements, subdivision construction plans are available for review in the Lake County Public Works Department located at 323 N. Sinclair Avenue in Tavares.
- 3. Driveways are not permitted in the radius return of an intersection. With the exception of joint driveways, driveway aprons must be 100 feet from the nearest intersecting road and 10 feet from the nearest property corner. The driveway width at the property line may not exceed 24 feet (10 feet minimum) and shall include either the standard minimum radius of 8 feet or 8 foot long by 4 foot wide flares on either side of the driveway, for a maximum width of 32' at the edge of the roadway. Variance requests should be submitted to the Lake County Public Works Department.
- 4. Pavers installed as a driveway apron are the resident's responsibility to maintain, replace and/or repair. If pavers are removed to facilitate Lake County and/or a utility company to perform utility installation and/or maintenance, the paver(s) used as replacements may not be able to be matched.
- 5. If a culvert pipe is required, it shall be the same diameter of existing culverts in neighborhood. If there are no other culverts in the neighborhood, the culvert pipe shall be a minimum of 15 inches in diameter and a minimum of 30 feet in length measured from the end of miter to the end of miter. All right-of-way must be restored to its original condition and in accordance to applicable Lake County Codes. All disturbed areas must be sodded, matching existing grass type. Applicant shall be responsible for sod until it is established.
- 6. Driveway apron slope may not exceed 14%. Variance requests should be submitted to the Lake County Public Works Department. In areas where sidewalks are present or planned, the driveway must include a minimum 4 foot wide path traversing the driveway apron (at a maximum 1.5% cross slope) in compliance with ADA requirements.
- 7. Driveway permit shall expire one (1) year from date approved.

8. Driveway Apron Permit Application shall include a check made payable to the Lake County Board of County Commissioners (BOCC).

I have read and understand the above requirements

Applicant's Signature/Date

Public Works Department Road Operations Division Residential Driveway Apron Permit Effective February 2017